

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 191 077 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
27.03.2002 Bulletin 2002/13

(51) Int Cl.7: **C09D 11/00, B41J 2/175,
B41J 2/21, B41M 5/00**

(21) Application number: **01122858.2**

(22) Date of filing: **24.09.2001**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **25.09.2000 JP 2000290559
26.09.2000 JP 2000292968**

(71) Applicant: **CANON KABUSHIKI KAISHA
Ohta-ku, Tokyo (JP)**

(72) Inventors:
• **Katsuragi, Ryuji, c/o Canon Kabushiki Kaisha
Tokyo (JP)**

• **Shioya, Makoto, c/o Canon Kabushiki Kaisha
Tokyo (JP)**
• **Yokoi, Hideto, c/o Canon Kabushiki Kaisha
Tokyo (JP)**

(74) Representative:
**Leson, Thomas Johannes Alois, Dipl.-Ing.
Tiedtke-Bühling-Kinne & Partner GbR,
TBK-Patent,
Bavariaring 4
80336 München (DE)**

(54) **Liquid composition, ink for ink-jet, ink set for ink-jet recording, ink-jet recording method, recording unit, ink cartridge, and ink-jet recording apparatus**

(57) A liquid composition for ink-jet recording, or an ink set for ink-jet recording which produces an image having water resistance and excellent print quality, and which can reduce color bleeding that occurs in formation of color images, and furthermore, which can extend a life-span of ink-jet recording heads, as well as an ink-jet recording method, a recording unit, an ink cartridge and

an ink-jet recording apparatus are provided. The liquid composition or a color ink constituting the ink set comprising a polyvalent metal salt, a material selected from the group consisting of acids including amino groups and salts thereof, and a liquid medium is used.

EP 1 191 077 A1

Description**BACKGROUND OF THE INVENTION****Field of the Invention**

[0001] The present invention relates to a liquid composition, an ink for ink-jet, an ink set for ink-jet recording, an ink-jet recording method, a recording unit, an ink cartridge, and an ink-jet recording apparatus. In particular, the present invention relates to a liquid composition, which: has water resistance and excellent print quality; reduces color bleeding that occurs in formation of color images; and can extend a life-span of ink-jet recording heads using thermal energy, as well as to an ink for ink-jet, an ink set for ink-jet recording, an ink-jet recording method using one of these, a recording unit, an ink cartridge, and an ink-jet recording apparatus.

Description of Background Art

[0002] The ink-jet recording method makes it easy to miniaturize an apparatus, to reduce running cost, to colorize, etc., and has the superiority in the formation of color images, although there are some problems under circumstances where improvement of image quality is further required. For example, when two different inks are applied on a recording medium adjacently to each other, there is a problem in that those inks are mixed with each other at the boundary therebetween, and as a consequent, a phenomenon of degradation of color image quality (bleeding) occurs. In particular, since color mixing at the boundary between black ink and color ink has a large effect on the degradation of image quality, various methods for solving the problems have been developed.

[0003] For example, as described in Japanese Patent Laid-Open No. 5-202328, US Patent No. 5198023, and Japanese Patent Laid-Open No. 6-106841, a technique for controlling the color bleeding by concurrent use of a first liquid containing a precipitant and a second liquid containing a coloring agent, which can produce precipitates by the precipitant, has been disclosed. As this precipitant, polyvalent metal salts have been disclosed, and as the coloring agent, which can produce precipitates by the polyvalent metal salts, dyes including at least one carboxylic group, etc., have been disclosed. Furthermore, the first liquid may include the coloring agent, and in this case, the first liquid can also be used as the ink.

SUMMARY OF THE INVENTION

[0004] However, according to research by the inventors of the present invention, it was discovered that when a solution containing a polyvalent metal salt, as described in Japanese Patent Laid-Open No. 5-202328 in order to prevent the aforementioned bleeding, was repeatedly ejected by a bubble-jet method, sometimes, kogation derived from the polyvalent metal salt were formed on a heater contacting with the solution containing the polyvalent metal salt. As a result, the quantity of the ejected liquid droplets and the speed of the ejected liquid droplets were reduced compared to those at the initial stage so as to cause a problem in that the image quality was affected. In addition, it has been observed that kogation sometimes causes breaks in the heater so as to prevent ejection of the polyvalent metal salt solution.

[0005] It is believed that the cause of the aforesaid ejection problems is the overheating of the ink or the liquid composition containing polyvalent metal salts, by the heater, which volatilizes or breaks down the anions constituting the polyvalent metal salts, and therefore, increasing the concentration of cation ions (polyvalent metal ions) around the heater. As a result, the alkalinity is also increased causing the outermost surface protection film, typically made of a metal, such as, for example, tantalum, and metal oxides, to dissolve.

[0006] Therefore, the inventors of the present invention earnestly researched regarding liquid compositions or inks which: have an effect of alleviating bleeding; prevent breaks of heaters and kogation; and can extend a life-span of recording heads. As a consequence, the present invention has been made. Accordingly, it is an object of the present invention to provide a liquid composition which can extend the life-span of an ink-jet recording head and can form high-quality images when used in an ink-jet recording method together with an ink.

[0007] Another object of the present invention is to provide an ink set which can extend the life-span of an ink-jet recording head, and can form high quality images.

[0008] A further object of the present invention is to provide an ink-jet recording method, a recording unit, an ink cartridge, and an ink-jet recording apparatus which can provide high quality images and extend the life-span of an ink-jet recording head.

[0009] The above objects are achieved by the present invention as described below.

[0010] According to one aspect of the present invention, there is provided a liquid composition for ink-jet recording which is used together with a color ink and reacts with the color ink when it comes into contact with the color ink, the

liquid composition comprising (a) a polyvalent metal salt, (b) a material selected from the group consisting of acids including amino groups and salts thereof, and (c) a liquid medium.

[0011] According to another aspect of the present invention, there is provided an ink-jet recording method comprising the steps of: (i) ejecting aforementioned liquid composition toward a recording medium by applying energy to the liquid composition; and (ii) ejecting aforementioned color ink toward a recording medium by applying energy to the color ink, wherein the steps are performed so that the liquid composition and the color ink form a contact state on the recording medium.

[0012] According to further aspect of the present invention, there is provided an ink set for ink-jet recording comprising: (1) the aforementioned liquid composition and (2) a color ink which comprises a coloring material and a liquid medium, and reacts with the liquid composition by contact with the liquid composition.

[0013] According to still further aspect of the present invention, there is provided a recording unit comprising: a liquid composition container portion containing the aforementioned liquid composition; an ink container portion containing a color ink which reacts with the liquid composition by contact with said liquid composition; and an ink-jet recording head for ejecting each of the liquid composition and the color ink by applying energy to the liquid composition and the color ink.

[0014] According to still further aspect of the present invention, there is provided an ink cartridge comprising: a liquid composition container portion containing the aforementioned liquid composition; and an ink container portion containing a color ink which comprises a coloring material and a liquid medium, and reacts with the liquid composition by contact with the liquid composition.

[0015] According to still further aspect of the present invention, there is provided an ink-jet recording apparatus comprising: a liquid composition container portion containing a liquid composition; an ink container portion containing a color ink which reacts with the liquid composition by contact with the liquid composition; and an ink-jet recording head for ejecting each of the liquid composition and the color ink by applying energy to the liquid composition and the color ink, wherein the liquid composition is the aforementioned liquid composition.

[0016] According to still further aspect of the present invention, there is provided an ink set for ink-jet recording comprising: (1) a color ink comprising a coloring material, a liquid medium, a polyvalent metal salt, and a material selected from the group consisting of acids including amino groups and salts thereof; and (2) a black ink which comprises a coloring material and a liquid medium, and reacts with the color ink by contact with the color ink.

[0017] According to still further aspect of the present invention, there is provided an ink-jet recording method comprising the steps of: (i) ejecting the aforementioned black ink toward a recording medium by applying energy to the black ink; and (ii) ejecting the aforementioned color ink toward a recording medium by applying energy to the color ink, wherein the steps are performed so that the black ink and the color ink form a contact state on the recording medium.

[0018] According to another aspect of the present invention, there is provided a recording unit comprising ink container portions containing each of the inks constituting an ink set and an ink-jet recording head for ejecting each of the inks supplied from the ink container portions by applying energy to the inks.

[0019] According to further aspect of the present invention, there is provided an ink cartridge comprising ink container portions containing each of the inks constituting an ink set.

[0020] According to still further aspect of the present invention, there is provided an ink-jet recording apparatus comprising: an ink container portion containing an ink set comprising at least a black ink and a color ink; and an ink-jet recording head for ejecting each of the inks supplied from the ink container portion by applying energy to the inks, wherein the ink set is the aforementioned ink set.

[0021] According to still further aspect of the present invention, there is provided an ink for ink-jet comprising: (a) a polyvalent metal salt, (b) a material selected from the group consisting of acids including amino groups and salts thereof, (c) a coloring material, and (d) a liquid medium.

[0022] Further objects, features and advantages of the present invention will become apparent from the following description of the preferred embodiments with reference to the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0023] Fig. 1 is a vertical sectional view of an embodiment of a recording head of an ink-jet recording apparatus according to the present invention.

[0024] Fig. 2 is a horizontal sectional view of an embodiment of a recording head of an ink-jet recording apparatus according to the present invention.

[0025] Fig. 3 is an external perspective view of a head in which the recording head according to the present invention as shown in Fig. 1 is multiplied.

[0026] Fig. 4 is a schematic perspective view of an embodiment of an ink-jet recording apparatus according to the present invention.

[0027] Fig. 5 is a perspective view of the internal configuration of an embodiment of an ink cartridge.

[0028] Fig. 6 is a perspective view of an embodiment of a recording unit.

- [0029] Fig. 7 is a perspective view of a recording portion in which a plurality of recording heads are arranged.
 [0030] Fig. 8 is a perspective view of another recording head used for the present invention.
 [0031] Fig. 9 is a diagram of a first configuration of a recording head.
 [0032] Fig. 10 is a diagram of a second configuration of a recording head.
 5 [0033] Fig. 11 is a diagram of a third configuration of a recording head.
 [0034] Fig. 12 is a perspective view of a recording portion in which a plurality of recording heads are arranged.
 [0035] Fig. 13 is a perspective view of another recording head used for the present invention.
 [0036] Fig. 14 is a diagram of a fourth configuration of a recording head.
 [0037] Fig. 15 is a diagram of a fifth configuration of a recording head.
 10 [0038] Fig. 16 is a schematic diagram of an ink-jet recording method according to an embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

15 [0039] The present invention will be explained below in detail using preferred embodiments.


First Embodiment

20 [0040] In accordance with a preferred embodiment of the present invention, recording is performed by applying: (1) a liquid composition composed of (a) a polyvalent metal salt, (b) a material selected from the group consisting of acids including amino groups and salts thereof, and (c) a liquid medium; and (2) a color ink on a recording medium so as to contact each other. The liquid composition preferably does not affect the color tone of the color ink in a recording image.

25 [0041] The (a) polyvalent metal salt will be described. Examples of suitable polyvalent metal salts include, magnesium salts, calcium salts, barium salts, iron(II) salts, copper(II) salts, zinc salts, aluminum salts, etc., of inorganic acids, for example, hydrochloric acid, nitric acid, and sulfuric acid, organic acids, for example, acetic acid and hydroxycarboxylic acid, or polyol phosphate. Among these polyvalent metal salts, those having a high solubility relative to the liquid medium such as, for example magnesium salts and calcium salts of nitric acid, magnesium salts and calcium salts of acetic acid, magnesium salts and calcium salts of hydroxycarboxylic acid, and magnesium salts and calcium salts of polyol phosphate are preferred.

30 [0042] Regarding the aforementioned hydroxycarboxylic acid, suitable examples include, aldaric acids (polyoxydicarboxylic acids), e.g., lactic acid, malic acid, citric acid, and tartaric acid, and aldonic acids, e.g., gluconic acid. Among these hydroxycarboxylic acids, polyvalent metal salts of aldonic acids, which have superior solubility and high degree of safety, are preferred.

35 [0043] The polyvalent metal salts of aldonic acids will be described in more detail below. The aldonic acids are polyoxycarboxylic acids corresponding to aldoses in which aldehyde groups have been oxidized to carboxylic groups. Since the aldonic acids make soluble polyvalent metal salts by bonding with polyvalent metal ions of magnesium, calcium, etc., the aldonic acids are appropriately used as constituents of the liquid composition according to the present invention. The aldonic acids are represented by the following general formula.



40
 45
 50 (Wherein n designates 0 or a positive integer, and *C designates an asymmetric carbon atom.)

[0044] As described above, since the aldonic acids have asymmetric carbon atoms, there are many optical isomers. The aldonic acids having 5 or more carbons (in the aforementioned general formula, n is 3 or more) are hardly present alone in aqueous solutions. It is said that, usually, a part of the aldonic acids form lactones with γ - or δ -hydroxyl groups, and become γ -aldonic lactones and δ -aldonic lactones, respectively, so as to present as a ternary equilibrium mixture of aldonic acids, γ -aldonic lactones, and δ -aldonic lactones. Likewise, the aldonic acids having 4 carbons (in the aforementioned general formula, n is 2) are hardly present alone in aqueous solutions. It is said that, usually, a part of the aldonic acids form lactones with γ -hydroxyl groups, and become respective γ -aldonic lactones, so as to present as a binary equilibrium mixture of aldonic acids and γ -aldonic lactones.

[0045] The aldonic acids are classified based on the number of carbons they contain. The aldonic acids having 4 carbons (in the aforementioned general formula, n is 2) are collectively called tetrionic acid, the aldonic acids having 5 carbons (in the aforementioned general formula, n is 3) are collectively called pentonic acid, and the aldonic acids having 6 carbons (in the aforementioned general formula, n is 4) are collectively called hexonic acid. Specific examples of the aldonic acid include, for example, glycolic acid (sometimes called hydroxyacetic acid) having 2 carbons (in the aforementioned general formula, n is 0), glyceric acid having 3 carbons (in the aforementioned general formula, n is 1), erythronic acid and threonic acid having 4 carbons (in the aforementioned general formula, n is 2), ribonic acid, arabonic acid, xylonic acid, and lyxonic acid having 5 carbons (in the aforementioned general formula, n is 3), gluconic acid, allonic acid, altronic acid, mannonic acid, gulonic acid, idonic acid, galactonic acid, and talonic acid having 6 carbons (in the aforementioned general formula, n is 4), and glucoheptonic acid having 7 carbons (in the aforementioned general formula, n is 5). Further and some of these may have each of D body, L body, and DL body.

[0046] Among the aldonic acids suitable as constituents of the liquid composition according to the present invention, especially preferable is gluconic acid (in the aforementioned general formula, n is 4) which will be described. Gluconic acid has been widely used as a food additive, and it is harmless to the human body. Gluconic acid rarely present alone in aqueous solutions. It is said that, usually, a part of gluconic acid form lactones with γ - or δ -hydroxyl groups, and become γ -gluconic lactone and δ -gluconic lactone, respectively, so as to present as a ternary equilibrium mixture of gluconic acid, γ -gluconic lactone, and δ -gluconic lactone. Regarding gluconic acid, there are D body, L body, and DL body, and any of these can be used, although D-glucose, which is D body, is generally easily available. There are, for example, allonic acid, altronic acid, mannonic acid, gulonic acid, idonic acid, galactonic acid, and talonic acid, as optical isomers of gluconic acid. Since these exhibit characteristics similar to those of gluconic acid, these may be used.

[0047] As the polyvalent metal salt of the aforementioned gluconic acid, magnesium gluconate, calcium gluconate, barium gluconate, iron(II) gluconate, copper(II) gluconate, etc., may be used, although the use of magnesium gluconate and calcium gluconate is preferred. Further, these compounds can be used alone or at least two of these can also be used concurrently.

[0048] The polyvalent metal salt of polyol phosphate will be described. Examples of suitable polyol phosphates include, for example, phosphate of polyol, monosaccharide, oligosaccharide, and polysaccharide, can be mentioned. Specifically, for example, glycerophosphoric acid, glucose-1-phosphate, glucose-6-phosphate, mannose-6-phosphate, galactose-6-phosphate, fructose-6-phosphate, glucose-1,6-diphosphate, fructose-1,6-diphosphate, ascorbic acid phosphate, sucrose phosphate, sorbitol phosphate, phosphorylated polyglycerin, and phosphorylated polyethylene glycol.

[0049] Among these, glycerophosphoric acid is preferable in the present embodiment, and will be described. Regarding glycerophosphoric acid, there are isomers, that is, α -glycerophosphoric acid and β -glycerophosphoric acid. In the present invention, either isomer can be used, and a mixture of the isomers may also be used. Suitable polyvalent metal salts of these glycerophosphoric acids include, for example, magnesium glycerophosphate, calcium glycerophosphate, barium glycerophosphate, iron(II) glycerophosphate, and copper(II) glycerophosphate. In particular, it is more preferable to use magnesium glycerophosphate and calcium glycerophosphate.

[0050] In the liquid composition according to the present invention, the total content of at least one compound selected from the aforementioned polyvalent metal salts is preferably 0.005% to 20% by mass based on the total amount of the liquid composition, more preferably is 0.05% to 12% by mass based on the total amount of the liquid composition, in order to achieve superior effect of reducing the bleeding and superior durability of the head.

[0051] Next, (b) a material selected from the group consisting of acids including amino groups and salts thereof, which constitutes the liquid composition according to the present invention, will be explained. Suitable acids including the amino group include, for example, amidosulfuric acid (sometimes called sulfamic acid), aminomethanesulfonic acid, taurine (sometimes called 2-aminoethanesulfonic acid), carbamic acid, glycine, alanine, β -alanine, aspartic acid, glutamic acid, sulfanilic acid, phenylalanine, leucine, isoleucine, threonine, tryptophan, valine, methionine, lysine, and arginine.

[0052] Among these, from the viewpoint of solubility relative to the liquid medium and available ease, it is preferable to use amidosulfuric acid (sulfamic acid), aminomethanesulfonic acid, taurine (2-aminoethanesulfonic acid), carbamic acid, glycine, alanine, β -alanine, aspartic acid and glutamic acid.

[0053] When the aforementioned salts of the acid including the amino group are used, commercially available salt compounds may be used, and organic acid salts formed by addition of alkali may be used. Suitable alkali agents include, for example, lithium hydroxide, sodium hydroxide, potassium hydroxide, aqueous ammonia (or ammonium hydroxide), magnesium hydroxide, calcium hydroxide, and organic amines (for example, triethanolamine, diethanolamine, monoethanolamine, diisopropanolamine, triisopropanolamine, tetramethylammoniumhydroxide, tetraethylammoniumhydroxide, and tetra- n -propylammoniumhydroxide). These compounds can be used alone, and at least two of these can also be used concurrently.

[0054] The total content of the aforementioned materials selected from the group consisting of acids including amino groups and salts thereof in the liquid composition is preferably between 0.005% to 20% by mass based on the total

amount of the liquid composition, and more preferably is between 0.05% to 12% by mass based on the total amount of the liquid composition, in order to achieve superior effect of reducing the clogging and extending a life-span of heads.

[0055] The ink-jet recording method according to the present invention is an ink-jet recording method in which images are recorded on a recording medium by applying energy for ejection to the ink, and subsequently, by ejecting the ink. The liquid composition according to the present embodiment having the aforementioned configuration and the color ink as described below are used concurrently, and these are applied on a recording medium so as to form a contact state of the liquid composition and the color ink on the recording medium, and perform recording. The coloring material used for the color ink will be explained below.

[0056] The color ink used together with the liquid component according to the present embodiment will be explained. The color ink comprises at least a coloring material and a liquid medium. When this ink contacts with the liquid component according to the present embodiment, it reacts with polyvalent metal so as to cause coagulation or precipitation of coloring materials in the color ink, or cause increase in viscosity of the color ink. As the coloring material of the color ink, pigments and dyes can be used. As the pigment, inorganic pigments, organic pigments, and other every pigment can be used, and the following examples are mentioned.

Carbon Black


C.I. Pigment Yellow 1, 2, 3, 12, 13, 14, 16, 17, 73, 74, 75, 83, 93, 95, 97, 98, 114, 128, 129, 151, 154, and 195,
C.I. Pigment Red 5, 7, 12, 48(Ca), 48(Mn), 57(Ca), 57:1, 57(Sr), 112, 122, 123, 168, 184, and 202,
C.I. Pigment Blue 1, 2, 3, 15:3, 15:34, 16, 22, and 60,
C.I. Vat Blue 4 and 6

[0057] When the aforementioned pigments are used as coloring materials, in order to stably disperse the pigments in the color inks, it is preferable to use dispersing agents. As the dispersing agent, macromolecular dispersing agents, surfactant dispersing agents, etc., can be used. Examples of suitable macromolecular dispersing agents include polyacrylates, styrene-acrylic acid copolymer salts, styrene-methacrylic acid copolymer salts, styrene-acrylic acid-acrylate copolymer salts, styrene-maleic acid copolymer salts, acrylate-maleic acid copolymer salts, styrene-methacrylsulfonic acid copolymer salts, vinyl naphthalene-maleic acid copolymer salts, β -naphthalenesulfonic acid formalin condensate salts, polyvinyl pyrrolidone, polyethylene glycol, and polyvinyl alcohol. Among these, it is preferable to use those having a weight average molecular weight of 1,000 to 30,000 and an acid value of 100 to 430. Examples of suitable surfactant dispersing agents include lauryl benzenesulfonates, lauryl sulfonates, lauryl benzenecarboxylates, lauryl naphthalenesulfonates, aliphatic amine salts, and polyethyleneoxide condensates. Regarding the usage of these dispersing agents, the content thereof preferably falls in the range satisfying the relationship, weight of the pigment : weight of the dispersing agent = 10 : 5 to 10 : 0.5.


[0058] In the present embodiment, as the coloring material of the color ink, self-dispersion type carbon black as described in Japanese Patent Laid-Open No. 5-186704 and Japanese Patent Laid-Open No. 8-3498, the disclosures of which are incorporated herein by reference to the extent that they describe how water-soluble groups are introduced to the surface of the carbon black so as to make self-dispersion possible, can be used. When the aforementioned self-dispersion type carbon black is used as the coloring material, since the aforementioned dispersing agent is not necessarily used, the usage of the dispersing agent can be reduced or obviated altogether. It is believed that when the aforementioned pigment ink contacts with the liquid composition according to the present embodiment, pigments in the pigment ink promptly coagulate and precipitate due to salting out effect, etc., of polyvalent metal ions in the liquid composition, and as a consequent, the speed of fixation of the coloring material in the pigment ink to a recording medium is increased, and even when at least two inks having different colors are adjacently applied, bleeding is not likely to occur. In the present embodiment, when the state of dispersion of the pigment has become unstable based on the aforementioned function, it is assumed that reaction between the color ink and the liquid composition has occurred.

[0059] When the dye is used as the coloring material in the color ink according to the present embodiment, water-soluble dyes are preferably used. For example, direct dyes, acidic dyes, basic dyes, dispersion dyes, and other every dye can be used. As the color ink including the dye as the coloring material, the one, in which precipitation of the dye due to salting out effect, formation of salts or compounds, that are not likely to dissolve in water or are insoluble in water, due to the reaction between polyvalent ions and dyes, or fixation of the dye in the color ink to the recording medium due to combination of these functions promptly proceed by the contact with the liquid composition according to the present embodiment, is appropriately used. As the dye usable for the aforementioned color ink, a dye including at least one carboxyl group in the molecule is preferable, because when it contacts with the liquid composition according to the present embodiment, it is likely to react with the polyvalent metal salt in the liquid composition so as to form an insoluble salt or compound. Specifically, it is preferable to use dyes having structures as shown by the following Example Compounds 1 to 30, although the present invention is not limited to these.


Example Compound 1



Example Compound 2




Example Compound 3




(Wherein M designates an alkali metal, an ammonium, or an organic ammonium.)

Example Compound 4




(Wherein M designates an alkali metal, an ammonium, or an organic ammonium.)

Example Compound 5




(Wherein M designates an alkali metal, an ammonium, or an organic ammonium.)


Example Compound 6




Example Compound 7




Example Compound 8




Example Compound 9




Example Compound 10




Example Compound 11




Example Compound 12




Example Compound 13




Example Compound 14




Example Compound 15




Example Compound 16




Example Compound 17




Example Compound 18




Example Compound 19




Example Compound 20




Example Compound 21




Example Compound 22




Example Compound 23




Example Compound 24




Example Compound 25




Example Compound 26




Example Compound 27




Example Compound 28



Example Compound 29



Example Compound 30



15 **[0060]** These Example Compounds may be used alone, or at least two of these may be used in combination, as the color material included in the color ink according to the present embodiment. The concentrations of these dyes and pigments are, usually, appropriately specified in the range of 0.1% to 20% by mass based on the total amount of the ink.

20 **[0061]** Next, the liquid composition according to the present embodiment, and the liquid medium used for the color ink used in the present embodiment will be explained. As the liquid medium, it is preferable to concurrently use water and a water-soluble organic solvent. Regarding the water used in the present embodiment, it is preferable to use deionized water rather than common water including various ions. The content of the water is preferably within the range of 35% to 96% by mass based on the total amount of the ink.

25 **[0062]** Since the water-soluble organic solvent can control the viscosity of the ink at a preferable viscosity suitable for use, it is used for various purposes, such as, for example, for reducing a drying speed of the ink, for preventing clogs of the nozzle of the recording head by increasing the solubility of the coloring material, etc. Suitable water-soluble organic solvents include, for example, alkyl alcohols having 1 to 5 carbons, e.g., methyl alcohol, ethyl alcohol, n-propyl alcohol, isopropyl alcohol, n-butyl alcohol, sec-butyl alcohol, tert-butyl alcohol, isobutyl alcohol, and n-pentanol, amides, e.g., dimethylformamide and dimethylacetamide, ketones or keto-alcohols, e.g., acetone and diacetone alcohol, ethers, e.g., tetrahydrofuran and dioxane, oxyethylene or oxypropylene copolymers, e.g., diethylene glycol, triethylene glycol, tetraethylene glycol, dipropylene glycol, tripropylene glycol, polyethylene glycol, and polypropylene glycol, alkylene glycols in which alkylene group has 2 to 6 carbon atoms, e.g., ethylene glycol, propylene glycol, trimethylene glycol, triethylene glycol and 1,2,6-hexane triol, glycerin, trimethylolethane and trimethylolpropane, lower alkyl ethers, e.g., ethylene glycol monomethyl(or ethyl) ether, diethylene glycol monomethyl(or ethyl) ether, and triethylene glycol monomethyl(or ethyl) ether, lower dialkyl ethers of polyhydric alcohol, e.g., triethylene glycol dimethyl(or ethyl) ether and tetraethylene glycol dimethyl(or ethyl) ether, alkanolamines, e.g., monoethanolamine, diethanolamine, and triethanolamine, sulfolane, N-methyl-2-pyrrolidone, 2-pyrrolidone, and 1,3-dimethyl-2-imidazolidinone. The aforementioned water-soluble organic solvent may be used alone, or may be used as a mixture.

35 **[0063]** In order to keep the pH of the color ink according to the present embodiment constant so as to stabilize the solubility of the dye and the dispersibility of the pigment in the ink, a pH regulator may be contained in the color ink. Suitable pH regulators include, for example, hydroxides, e.g., lithium hydroxide, sodium hydroxide, potassium hydroxide, and ammonium hydroxide, sulfates, e.g., lithium sulfate, sodium sulfate, potassium sulfate, and ammonium sulfate, carbonates, e.g., lithium carbonate, sodium carbonate, sodium hydrogencarbonate, potassium carbonate, potassium hydrogencarbonate, ammonium carbonate, and ammonium hydrogencarbonate, phosphates, e.g., lithium phosphate, sodium phosphate, disodium phosphate, trisodium phosphate, potassium phosphate, dipotassium phosphate, tripotassium phosphate, ammonium phosphate, diammonium phosphate, triammonium phosphate, acetates, e.g., lithium acetate, sodium acetate, potassium acetate, and ammonium acetate, and hydrochloride.

45 **[0064]** These pH regulators may be added into the liquid composition and the color ink alone, although it is more preferable to concurrently use at least two pH regulators selected from the aforesaid group. In order to keep the pH stable, to increase dissolution stability of the water-soluble dye included in the color ink, and to prevent problems of clogs of the nozzle, etc., these pH regulators are added preferably by 0.1% to 10% by weight, and more preferably, by 1% to 8% by weight.

50 **[0065]** Furthermore, in the liquid composition according to the present embodiment and the color ink used together therewith, in addition to the aforementioned components, if necessary, various publicly known and common additives, for example, viscosity regulators, fungicides, preservatives, antioxidants, antifoamers, and urea and other inhibitors of nozzle from drying, can be appropriately used concurrently.

55 **[0066]** Regarding the preferable range of properties of the liquid composition according to the present embodiment and the color ink used together therewith, the pH in the neighborhood of 25°C is preferably 3 to 12, and more preferably, is 4 to 10. The surface tension is preferably 10 to 60 mN/m (dyn/cm), and more preferably, is 15 to 50 mN/m (dyn/cm).

The viscosity is preferably 1 to 30 cps, and more preferably, is 1 to 10 cps.

[0067] Regarding the ink-jet recording method according to the present embodiment, the liquid composition having the aforementioned configuration and the color ink are concurrently used, and these are applied on a recording medium while contact and reaction occur therebetween, so as to perform the recording. The recording medium used at that time is not specifically limited. However, the ink-jet recording method according to the present embodiment is especially suitable for conventionally used so-called plain papers, such as copying papers and bond papers, because reducing effect on bleeding is remarkably exhibited when images are formed on these papers.

[0068] The ink-jet recording method according to the present embodiment is a method in which the ink is ejected by applying energy for ejection to the ink so as to record the image on the recording medium. In particular, regarding the ink-jet recording method in which thermal energy is used for ejecting the ink, when the image is formed using the recording method according to the present embodiment, superior prevention of so-called fogging can be achieved. As the ink-jet recording method using thermal energy, for example, so-called on-demand type bubble-jet method, in which liquid droplets are ejected using bubble generated by thermal energy, may also be used.

[0069] In the ink-jet recording method according to the present embodiment, regarding the order of application of the liquid composition and the color ink on the recording medium in forming the image, the liquid composition may be ahead of the color ink, or the color ink may be ahead of the liquid composition, as long as the liquid composition having the aforementioned configuration and the color ink are concurrently used, and these are applied on a recording medium while contact and reaction occur therebetween, so as to perform the recording. That is, in the present embodiment, regardless of the order and method of application thereof, by applying the liquid composition on the recording medium, while being contacted with the color ink, excellent print quality and improved: fixation; water resistance; and prevention of bleeding of the image formed by the color ink are achieved. It is believed that the reason for these results include, inter alia, that the polyvalent metal ions in the liquid composition and pigments and dyes in the color ink are mixed on the recording medium so as to cause coagulation, precipitation, or increase in viscosity of the color ink.

[0070] In particular, from the viewpoint of further improvement of image density and fixation property, for example, it is more preferable to apply the liquid composition after application of the color ink, and subsequently, to further apply the color ink. The color ink may be applied on the recording medium after application of the liquid composition, and subsequently, the liquid composition may be further applied.

[0071] In the case where the application of the liquid composition is ahead of the application of the color ink, the time interval between the adhesion of the liquid composition on the recording medium and the adhesion of the color ink is not specifically limited, although, in order to make the present invention further effective, it is preferably within a few seconds, and more preferably, is within one second. This may also be applied to the case where the application of the liquid composition and the application of the color ink are performed on the recording medium in reverse order. Furthermore, as shown in Fig. 16, each of the liquid composition 804 and the color ink 805 may be ejected from respective recording heads 801 and 802 of the ink-jet recording apparatus, and immediately after the ejection, these may be mixed 806 and applied on the recording medium 803.

[0072] As described above, according to the ink-jet recording method of the present embodiment, regardless of the order and method of the application of the liquid composition and the color ink, by concurrently applying the liquid composition composed of specified components according to the present embodiment and the color ink used together therewith on a recording medium, excellent print quality, and improved fixation, water resistance of the image formed by the color ink, and prevention of bleeding during formation of the color image. It is believed that these advantages because polyvalent metal ions contained in the liquid composition and pigments, dyes, or pigments and dyes in the color ink are mixed so as to form coagulates, and as a consequence, the aforementioned superior effects are achieved.

[0073] In the ink-jet recording method according to the present embodiment, when the liquid composition and the color ink are applied on the recording medium and recording is performed by the aforementioned method, in the image formation region, the ratio of the application quantity of the color ink to that of the liquid composition per area of the recording medium may be 1 : 1, although the ratio of the color ink to the liquid composition may be 10 : 1 to 10 : 10. Herein, the control of the ratio of the application quantity of the color ink to that of the liquid composition per area of the recording medium can be performed by various methods including, for example, a method in which when the application of the liquid composition and the color ink on the recording medium is performed by the ink-jet recording method, the number of pixels of the liquid composition to be adhered on the recording medium is controlled in the range of 10% to 100% of the number of pixels of the color ink to be adhered on the recording medium, a method in which when the application of the liquid composition and the color ink on the recording medium are performed by the ink-jet recording method, the ejection quantity of the liquid composition is controlled to be smaller than the ejection quantity of the color ink so as to make the number of pixels of the liquid composition to be adhered on the recording medium in the range of 10% to 100% of the number of pixels of the color ink to be adhered on the recording medium, or a method which is combination of the aforementioned methods.

[0074] The ink-jet recording method according to the present embodiment and the ink-jet recording apparatus applying this method will be explained below in further detail. In the ink-jet recording method according to the present

embodiment, the ink-jet recording method, in which energy is applied to the ink, and the ink is thereby ejected so as to form the image on the recording medium, is used as the method for adhering the liquid composition according to the present embodiment and the color ink on the recording medium. As the recording method, various publicly known conventional ink-jet methods such as, for example, an ink-jet recording method using mechanical energy due to deformation of a piezoelectric element, can be used. However, it is preferable to use an ink-jet recording method in which ink is ejected by the application of thermal energy.

[0075] That is, as described above, the occurrence of kogation caused when the image is formed by the ink-jet recording method, in which, in order to prevent color mixed bleeding between different colors and to improve water resistance of records, the color ink and the liquid composition containing polyvalent metal salts are used concurrently, and thermal energy is used to eject the liquid composition, and degradation of image quality accompanying this, can be effectively prevented by the ink-jet recording method according to the present embodiment in which the liquid composition according to the present embodiment is used. In contrast, in a conventional method, when the solution used together with the color ink in order to prevent bleeding and to improve water resistance of records was repeatedly ejected from the recording head, sometimes, the outermost surface protection layer made of at least one of metal or metal oxide, for example, made of at least one of tantalum or tantalum oxide, formed on the heater (heater element substrate) for applying thermal energy was dissolved, and accompanying this, breaks in the heater occurred so that ejection became impossible, and kogation occurred on the heater so as to affect quality of the formed image. However, these problems are effectively prevented by the present invention.

[0076] The ink-jet recording apparatus according to the present embodiment using the liquid composition according to the present embodiment includes a liquid composition storage portion storing the liquid composition, a color ink storage portion storing the color ink, and an ink-jet recording head that ejects each of the liquid composition and the color ink. As described above, a preferable embodiment is an apparatus which ejects the liquid composition and the color ink by function of thermal energy, and which is an ink-jet recording apparatus provided with a head for ink-jet recording including a heater in order to apply thermal energy to the liquid composition and the color ink in the flow path introduced from the aforementioned liquid composition storage portion and color ink storage portion and a device for applying an electrical pulse signal to the aforementioned heater responding to recording information, and furthermore, which is an ink-jet recording apparatus wherein the aforementioned heater has an outermost surface protection layer containing at least one of a metal and a metal oxide. In particular, when the metal and the metal oxide are tantalum and tantalum oxide in an embodiment of the ink-jet recording apparatus, the effects of the present invention are remarkably exhibited.

[0077] Furthermore, it has been observed that when the ink-jet recording apparatus is controlled so that the ratio of an energy E_{op} , which is input into the heater in order to eject the liquid composition, to the minimum energy input E_{th} , which is necessary for the heater to eject the ink from a recording head, E_{op}/E_{th} ($= r$ value), satisfies the relationship, $1.10 \leq E_{op}/E_{th} \leq 1.90$, the effects of the present invention are remarkably exhibited.

[0078] The ink-jet recording apparatus by application of the ink-jet recording method, in which the ink is ejected using thermal energy, will be explained below with reference to the drawings. Fig. 1 and Fig. 2 show an embodiment of a recording head that is a part of an ink-jet recording apparatus using thermal energy. Fig. 1 is a sectional view of a recording head 13 along an ink flow path. Fig. 2 is a sectional view of the section indicated by line II-II shown in Fig. 1. The head 13 is produced by adhering a glass, ceramic, silicon, polysulfone, or plastic board, etc., having a flow path (nozzle) 14 for ink and a heater element substrate 15. The heater element substrate 15 is composed of: (1) a protection layer 16-1 made of silicon oxide, silicon nitride, silicon carbide, etc.; (2) an outermost surface protection layer 16-2 made of metal, such as, for example, platinum, or a metal oxide, such as, for example, platinum oxide, especially, made of tantalum or tantalum oxide; (3) electrodes 17-1 and 17-2 made of, for example, aluminum, gold, aluminum-copper alloys, etc.; (4) a heating resistor layer 18 made of a high melting point material, such as, for example, hafnium boride, tantalum nitride, tantalum-aluminum, etc.; (5) a heat storage layer 19 made of, for example, silicon oxide, aluminum oxide, etc.; (6) and a substrate 20 made of a heat-dissipating material, such as, for example, silicon, aluminum, or aluminum nitride.

[0079] In the ink-jet recording apparatus using thermal energy, when an electrical pulse signal is applied to the electrodes 17-1 and 17-2 of the aforementioned head 13, a region of the heater element substrate 15 (heater) indicated by n is rapidly heated, and a bubble is generated in the ink 21 contacting with this surface. Subsequently, a meniscus 23 is extruded due to the pressure thereof, and the ink 21 is ejected through a nozzle 14 of the head, and travels as ink droplets 24 from an ejection orifice 22 toward a recording medium 25. Fig. 3 is an external perspective view of an embodiment of a multihead in which multiple recording heads, like the one shown in Fig. 1, are arranged. This multihead is produced by adhering a glass board 27 having a multinozzle 26 and a heater head 28 similar to that explained in Fig. 1.

Quantity of Energy Applied to Heater

[0080] Next, the r value will be explained. The r value is a factor representing a ratio of actually input energy to the

critical energy which is minimum energy required of the bubble-jet head for ejecting the ink or the liquid composition. That is, input energy E is represented by the following formula (A) using a width P of a pulse applied to the bubble-jet head (when a plurality of divided pulses are applied, total width is used), applied voltage V, and resistance R of the heater,

$$E = P \times V^2 / R \quad (A)$$

[0081] At this time, the r value is determined by the following formula (B) from the minimum energy E_{th} , which is necessary for the heater to eject the ink or the liquid composition from the bubble-jet head, and the energy E_{op} , which is actually input in order to drive,

$$r = E_{op} / E_{th} \quad (B)$$

[0082] As the method for determining the r value suitable for, for example, ejecting the liquid composition based on the driving conditions of the bubble-jet head, the following two methods (1) and (2) are performed in practice.

(1) When pulse width is fixed

[0083] A voltage suitable for ejecting the liquid composition from the bubble-jet head is determined using the specified pulse width, and ink ejection is started by driving the heater. Then, the voltage is gradually reduced to find the voltage at which the ejection stops, and the voltage immediately before the voltage at which ejection stops is assumed to be the minimum voltage V_{th} at which ejection is possible. When the voltage actually used for driving is indicated by V_{op} , the r value is determined by the following formula (C),

$$r = (V_{op} / V_{th})^2 \quad (C)$$

(2) When voltage is fixed

[0084] A pulse width suitable for ejecting the liquid composition from the bubble-jet head is determined using the specified voltage, and ink ejection as started by driving heater. Then, the pulse width is gradually reduced to find the pulse width at which the ejection stops. The pulse width immediately before the pulse width at which ejection stops is assumed to be the minimum pulse width P_{th} at which ejection is possible. When the pulse width actually used for driving is indicated by P_{op} , the r value is determined by the following formula (D),

$$r = P_{op} / P_{th} \quad (D)$$

[0085] Herein, the voltage is a voltage actually applied to the heater portion in order to heat the bubble-jet heater. Since the voltage applied from the outside of the head may be reduced due to contact and wiring resistance, etc., it cannot be used for calculating the r value in the strict sense. However, when V_{th} and V_{op} are measured from the outside of the head, since both measured values include the aforementioned voltage variation, even if these values are directly used for calculating the r value, error is small, as long as the voltage variation is not large. Therefore, these values can be used as the r value for convenience sake.

[0086] When recording is performed using a practical printer, since a plurality of heaters are driven, it must be noted that a voltage applied to one heater may vary as a result of variations between the individual heads.

[0087] From the aforementioned formulae (A) and (B), when the r value is the same, the square of V and P seem to be in inverse proportion, although, in practice, since there are electrical problems in that a pulse shape does not become rectangular, etc., thermal problems in that when pulse shapes are different, thermal diffusions in the periphery of heaters are different, etc., and problems specific to bubble-jet in that when voltages are different, heat fluxes from heaters to inks are different so as to cause variation in the states of bubbling, etc., the square of V and P are not in a simple relationship. Therefore, the methods described in the aforementioned (1) and (2) must be treated independently. It must be noted that conversion of one value to another value by calculation may cause an error. In the present invention, the r value was determined by the aforementioned method (1), unless otherwise specified.

[0088] In order to stably eject the ink and the liquid composition, it is general to drive under conditions where the r

value determined as described above is in the range of about 1.12 to 1.96. However, in the case where the liquid composition according to this embodiment of the present embodiment is ejected from the recording head due to application of thermal energy, by driving while the r value is in a predetermined range, specifically, in the range of 1.10 to 1.90, adhesion of kogation due to the ejection of the liquid composition to the heater is further prevented, and consequently, the life span of recording head can be further extended, so that this case is preferable.

[0089] Although the specific reasons adhesion of kogation to the heater can be especially effectively prevented, and consequently, the life span of recording head can be further increased when the liquid composition according to the present embodiment is ejected from the recording head due to application of thermal energy, while the r value is in the aforementioned range, are not certain, it is believed that, by driving while the r value is in the aforementioned range, first, at least one of acids including amino groups and salts thereof contained in the liquid composition according to the present embodiment protects the outermost surface protection layer with a result that erosion of at least one of metals and metal oxides thereof constituting the outermost surface protection layer is effectively prevented, and second, since the surface temperature of the heater is not excessively increased due to excessive supply of energy to the heater, erosion (dissolution) of metal due to increased alkalinity caused by polyvalent metal ions constituting the liquid composition used in order to prevent occurrence of color mixed bleeding and to improve water resistance of records does not excessively occur.

[0090] Fig. 4 shows an embodiment of an ink-jet recording apparatus in which the recording head as explained above is incorporated. In Fig. 4, an end of a blade 61 as a wiping member is held and fixed by a blade-holding member so as to have the form of a cantilever. The blade 61 is deployed at a position adjacent to a recording region for the recording head 65, and in the embodiment as shown in the drawing, the blade 61 is held protruding into the path of the movement of the recording head 65.

[0091] A cap 62 is a cap of an ejection outlet face of the recording head 65, and is deployed at the home position adjacent to the blade 61. The cap 62 moves in the direction perpendicular to the direction of the movement of the recording head 65 and contacts the ejection outlet face so as to perform capping. Ink absorbent 63 as shown in Fig. 4 is deployed adjacent to the blade 61, and is held protruding into the path of the movement of the recording head 65 in a manner similar to that of the blade 61.

[0092] An ejection recovery portion 64 is composed of the aforementioned blade 61, cap 62, and ink absorbent 63, and water, dust, and the like on the ink ejection outlet face are removed by the blade 61 and the ink absorbent 63.

[0093] The recording head 65 has an ejection energy generation device and ejects the ink toward the recording medium facing an ejection outlet face provided with an ejection outlet so as to perform the recording. A carriage 66 has a recording head 65 mounted on it so as to carry the recording head 65. The carriage 66 slidably engages a guide shaft 67, and a part of the carriage 66 connects with a belt 69 driven with a motor 68, although not shown in the drawing. Accompanying this, the carriage 66 can move along the guide shaft 67, and therefore, the recording head 65 can move to the recording region and the region adjacent thereto.

[0094] A feeder 51 inserts the recording material. A feed roller 52 is driven by a motor, which is not shown in the drawing. According to this configuration, the recording medium is fed to a position facing the ejection outlet face of the recording head 65, and is discharged to a discharge portion provided with a discharge roller 53 during the recording. Regarding the aforementioned configuration, when the recording head 65 returns to the home position in accordance with the completion of the recording, the blade 61 protrudes into the path of the movement of the recording head 65, while the cap 62 in the head recovery portion 64 recedes from the path of the movement. As a consequence, the ejection outlet face of the recording head 65 is wiped.

[0095] When the cap 62 contacts the ejection outlet face of the recording head 65 in order to perform capping, the cap 62 moves so as to protrude into the path of the movement of the recording head 65. When the recording head 65 moves from the home position to the recording start position, the cap 62 and the blade 61 are located at the same position as that in the aforementioned wiping. As a consequence, the ejection outlet face of the recording head 65 is also wiped during this movement. The recording head moves to the home position at the time of the completion of the recording and the ejection recovery. In addition to this, when the recording head moves between recording regions for recording, the recording head moves to the home position adjacent to the recording region at predetermined intervals so that the aforementioned wiping is also performed accompanying this movement.

[0096] Fig. 5 shows an embodiment of an ink cartridge 45 storing the ink to be supplied to the recording head through an ink supply member, such as, for example, a tube. Herein, the ink storage portion 40 storing the supply of ink may be, for example, an ink bag having a rubber stopper 42 at the end. The ink in the ink bag 40 can be fed to the head by a needle, (not shown in the drawing), inserted into the stopper 42. Ink absorbent 44 receives the waste ink. The face of the ink storage portion contacting the liquid is preferably made of polyolefin, and more preferably polyethylene.

[0097] The ink-jet recording apparatus according to the present embodiment is not limited to the aforementioned ink-jet recording apparatus in which the head and the ink cartridge are separated, and may be an ink-jet recording apparatus in which the head and the ink cartridge are integrated as shown in Fig. 6. In Fig. 6, an ink storage portion storing the ink, for example, an ink absorbent, is stored in a recording unit 70, and the ink in the ink absorbent is ejected

as ink droplets from a head portion 71 including a plurality of orifices. A preferable material for use as the ink absorbent is, polyurethane. A configuration in which the ink storage portion is an ink bag provided with a spring therein instead of the ink absorbent may be adopted. The inside of the cartridge is communicated with air through a ventilation hole 72. This recording unit 70 is used instead of the recording head 65 as shown in Fig. 4, and can be freely attached to or detached from the carriage 66.

[0098] When a color image is formed by the ink-jet recording method according to the present embodiment, for example, a recording apparatus in which five recording heads as shown in Fig. 3 are arranged on a carriage is used. Fig. 7 shows such an embodiment. Recording heads 91, 92, 93, and 94 eject yellow ink, magenta ink, cyan ink, and black ink, respectively. A head 95 ejects the liquid composition. These heads are deployed in the aforementioned recording apparatus, and eject each of inks responding to recording signals. The liquid composition is, for example, adhered to at least the image formation part of the recording medium on which the inks are adhered prior to the ejection of each of color inks.

[0099] Fig. 7 shows an embodiment using five recording heads, although it is important to note that the present invention is not limited to this, and, as shown in Fig. 8, it is also preferable to eject yellow 101, magenta 102, cyan 103, black 104, and liquid composition 105 from one recording head by separating liquid flow paths. The heads may be arranged so that the recording order of each ink and the liquid composition becomes the reverse of the aforementioned order.

[0100] As examples of specific arrangements of the ink-jet recording head appropriately used in the present embodiment, three configurations are shown in Figs. 9, 10, and 11. In Figs. 9, 10, and 11, reference numerals 111 to 114, 121 to 124, and 131 to 134 each indicates recording heads for ejecting coloring inks of yellow (Y), magenta (M), cyan (C) and black (Bk), respectively. Reference numerals 115, 125 and 135 designate recording heads for ejecting a liquid composition (S). Each of the recording heads is arranged on the carriage in a general manner similar to that as shown in Fig. 7, although the arrangements are different depending on configurations. Each of the recording heads is deployed in the aforementioned recording apparatus, and ejects each of the color inks responding to the recording signal. The liquid composition is adhered to at least the image formation part of the recording medium, on which the color inks are adhered, prior to, or after, the ejection of the color inks. Each of the recording heads moves with the carriage in the direction indicated by an arrow (1), and the recording medium moves with feed roller, etc., in the direction indicated by an arrow (2).

[0101] In a first configuration example, as shown in Fig. 9, recording heads S(115), Bk(114), C(113), M(112) and Y(111) are arranged on the carriage in parallel. In a second configuration example, as shown in Fig. 10, the recording heads for the liquid composition(125) and the black ink(124) are arranged in parallel, and recording heads C(123), M(122), and Y(121) are arranged in series with each other, and in parallel to the aforementioned recording heads. Herein, the ejection volume of each of the recording heads per 1 dot is not necessarily the same. The ejection volume (Vd) of each of the recording heads per 1 dot may be controlled depending on a composition of the liquid composition, etc., so that optimized recording is performed. Preferably, the recording heads S, Y, M, and C have the same Vd, and the Vd of the recording head is specified to be twice larger than that, although not limited to this. In a third configuration example, as shown in Fig. 11, recording heads Bk(134), S(135), Bk(134), C(133), M(132), and Y(131), each having the same ejection volume, are arranged in parallel on a carriage, and therefore, the ejection quantity of the black ink can be twice as much as the ejection quantity of the liquid composition and each of the color inks. In the configuration example shown in Fig. 11, the ejection volume (Vd) of each of the recording head S, Bk, Y, M, and C is not necessarily the same.

[0102] As described above, in the present embodiment, the ratio of the application quantity of the color ink, especially magenta ink, to that of the liquid composition per area of the recording medium may be 1 : 1 in the image formation region, although the ratio of the color ink to the liquid composition may range between 10 : 1 to 10 : 10. Herein, the control of the ratio of the application quantity of the color ink to that of the liquid composition per area of the recording medium can be performed by, specifically, for example, a method in which the number of pixels of the liquid composition to be adhered on the recording medium is controlled in the range of 10% to 100% of the number of pixels of the color ink to be adhered on the recording medium, a method in which, regarding the application of the liquid composition and the color ink, the ejection quantity of the liquid composition is controlled to be smaller than the ejection quantity of the color ink, or a method in which the aforementioned methods are combined, so that the number of pixels of the liquid composition to be adhered on the recording medium is controlled to be in the range of 10% to 100% of the number of pixels of the color ink to be adhered on the recording medium, and the ejection quantity of the liquid composition is controlled to be smaller than the ejection quantity of the color ink in the application of the liquid composition and the color ink on the recording medium.

Second Embodiment

[0103] As a second embodiment according to the present invention, an ink including a coloring material, a liquid

medium, a polyvalent metal salt, and a material selected from the group consisting of acids including amino groups and salts thereof will be explained. In the preferable embodiment using the aforementioned ink, the ink is color ink, and the ink set for ink-jet recording is composed of this color ink and black ink which includes a coloring material and a liquid medium, and reacts with the color ink on contact therewith. An embodiment using the aforementioned ink set will be explained below.

[0104] In the present embodiment, recording is performed by application of the color ink and the black ink, while a contact state of the color ink and the black ink is formed on the recording medium. It is an object of the ink set according to the present embodiment to alleviate bleeding between the black ink and the color ink. Regarding alleviation of bleeding among the color inks, for example, yellow ink, magenta ink, and cyan ink, no specific measure is taken, although the present invention is also effective on prevention of bleeding among the color inks to perform ink design by, for example, adding a surfactant into the color ink, in order to make the color ink rapidly penetrate plain paper.

[0105] The color ink constituting the ink set according to the present embodiment will be explained. The color ink used in the present embodiment includes a coloring material, a liquid medium, a polyvalent metal salt, and a material selected from the group consisting of acids including amino groups and salts thereof as described in detail in the aforementioned first embodiment.

[0106] The coloring material included in the color ink constituting the ink set according to the present embodiment will be explained. As the coloring material, direct dyes, acidic dyes, basic dyes, dispersion dyes, and pigments are mentioned, and it is preferable that even when the coloring material is blended with the polyvalent metal salt, it does not react and solubility is maintained. Suitable coloring materials include, for example, C.I. Acid Yellow 23, C.I. Acid Red 52 and 289, C.I. Acid Blue 9, C.I. Reactive Red 180, C.I. Direct Blue 189 and 199, C.I. Basic Yellow 1, 2, 11, 13, 14, 19, 21, 25, 32, 33, 36, and 51, C.I. Basic Orange 2, 15, 21, and 22, C.I. Basic Red 1, 2, 9, 12, 13, 37, 38, 39, and 92, C.I. Basic Violet 1, 3, 7, 10, and 14, C.I. Basic Blue 1, 3, 5, 7, 9, 19, 24, 25, 26, 28, 29, 45, 54, and 65, C.I. Basic Green 1 and 4, C.I. Basic Brown 1 and 12, and C.I. Basic Black 2 and 8, etc. These water-soluble dyes may be used alone, and at least two dyes may be used in combination. The concentrations of these water-soluble dyes are preferably within the range of 0.1% to 20% by mass relative to the total quantity of the ink.

[0107] In the color ink constituting the ink set for ink-jet recording according to the present invention, in addition to the aforementioned components, preferably, at least one surfactant is included. By including the surfactant, the color ink can be invested with a desired penetration property and viscosity. That is, as described above, it is an object of the ink set for ink-jet recording according to the present invention to prevent bleeding between the black ink and the color ink. Regarding prevention of bleeding among the color inks, for example, yellow ink, magenta ink, and cyan ink, no specific measure is taken. However, as described above, it is preferable to design the addition of the surfactant into the color ink, in order to make the color ink have rapid penetration property respect to sized plain paper, because degradation of print quality is not brought out by a large degree in practice.

[0108] Various publicly known conventional surfactants, such as, for example, anionic surfactants, cationic surfactants, and nonionic surfactants, may be used. Among these, nonionic surfactants are preferable. The quantities of these surfactants added into the color ink are not specifically limited, although in order to achieve a desired penetration property and an appropriate viscosity, it is preferably within the range of 0.01% to 10% by mass based on the total amount of the ink, and, more preferably, is within the range of 0.1% to 10%.

[0109] The black ink constituting the ink set for ink-jet recording according to the present embodiment will be explained. The black ink used in the present embodiment includes a coloring material, which reacts with the polyvalent metal, and a liquid medium. As the coloring material used in the black ink, black coloring materials usable for the color ink in the aforementioned first embodiment can be used. These coloring materials may be used alone, or at least two of these may be used in combination. The quantities of these coloring materials added to the ink are preferably within the range of 0.1% to 20% by mass based on the total amount of the ink.

[0110] In the present embodiment, preferably, a nonionic surfactant is further included in the black ink. Accompanying this, bleeding between the black ink and the color ink can be further prevented. Furthermore, by the addition of the nonionic surfactant, as described below, an effect of preventing reduction of the black ink density at the boundary between the black ink and the color ink, that is, occurrence of so-called white haze, can also be achieved.

[0111] In the color ink used for the ink set for ink-jet recording according to the present embodiment, as described above, in order to improve the characteristics as the ink for ink-jet recording, preferably, a surfactant is included, and many color inks have high penetration property into recording media, such as plain paper, and have low surface tensions. When the aforementioned color ink having a low surface tension and the black ink, used in the present invention, having a high surface tension are adjacent to each other, a region, in which there are few coloring materials, may be generated at a boundary adjacent to the black ink. As a consequence, a phenomenon called white haze may occur. Therefore, by adding the nonionic surfactant to the black ink so as to reduce the surface tension, the aforementioned white haze phenomenon can be prevented from occurring.

[0112] In the present embodiment, the content of the nonionic surfactant included in the black ink is not specifically limited as long as bleeding and white haze are prevented, although in order to further prevent bleeding between the

black ink and the color ink, to effectively prevent the occurrence of white haze, and to keep ink ejection property and print quality excellent, the content is preferably within the range of 0.1% to 0.5% by mass based on the total amount of the ink, and more preferably, is within the range of 0.2% to 0.4%.

[0113] Herein, as the nonionic surfactant, it is preferable to use nonionic surfactants of higher alcohol ethylene oxide adducts, such as, for example, alkylphenol ethylene oxide adducts, aliphatic ethylene oxide adducts, polyhydric alcohol aliphatic acid ester ethylene oxide adducts, aliphatic amide ethylene oxide adducts, higher alkylamine ethylene oxide adducts, polypropylene glycol ethylene oxide adducts, polyhydric alcohol aliphatic acid esters, and alkanolamine aliphatic amides. More preferably, nonionic surfactants of higher alcohol ethylene oxide adducts, alkylphenol ethylene oxide adducts, ethylene oxide-propylene oxide copolymer, acetylene glycol ethylene oxide adducts, etc., can be used.

[0114] As the liquid medium used in the black ink and color ink constituting the ink set for ink-jet recording according to the present embodiment, the liquid composition in the aforementioned first embodiment, and water-soluble solvents which was explained above in detail as the liquid media included in the color ink used together with the liquid composition, as well as additives, addition quantities, property values, etc., can be used.

[0115] The ink-jet recording method according to the present embodiment, and the ink-jet recording apparatus, which can realize the recording method, will be explained.

[0116] In the ink-jet recording method according to the present embodiment, the ink is ejected due to application of energy for ejection to the ink so as to record the color image on the recording medium, and the aforementioned ink set for ink-jet recording according to the present embodiment is used for the ink.

[0117] The recording medium used in the present embodiment is not specifically limited. However, in the present invention, especially, conventionally used so-called plain papers, such as copying papers and bond papers, are preferable, because the reduced effect of bleeding is exhibited when images are formed on these types of papers using the ink set according to the present invention. The ink set for ink-jet recording according to the present invention can also be appropriately used for, for example, coated papers and OHP transparency films, which are specifically produced for ink-jet recording, and furthermore, that can also be appropriately used for common high quality papers and calendar papers.

[0118] In the ink-jet recording method according to the present embodiment, as the method for applying the black ink and the color ink on the recording medium, a method, in which the black ink and the color ink are applied so as to contact with each other at boundary, can be used.

[0119] As another embodiment, a method in which the black ink (1) and the color ink (2) are applied so as to superimpose on each other on the recording medium, and the application of the color ink on the recording medium is performed prior to the application of the black ink (hereafter called as under pick method) can be used. By performing the under pick method, the bleeding between the black ink and the color ink can be improved, and furthermore, the aforementioned white haze can be reduced. In the aforementioned under pick method, the time interval between the adhesion of the color ink on the recording medium and the adhesion of the black ink is not specifically limited, although, it is preferably within a few seconds, is more preferably within one second in order to make the present invention even more effective. In an alternate embodiment, the color ink is applied after the application of the black ink (over pick), or the color ink and the black ink are mixed immediately after ejection thereof as shown in Fig. 16.

[0120] In the under pick method, the ratio of the application quantity of the black ink (1) to that of the color ink (2) per area of the recording medium may be 1 : 1 in the image formation region, although the ratio of the black ink (1) to the color ink (2) may be in the range of 10 : 1 to 10 : 10. Accompanying this, the white haze in the resulting image can be reduced, and especially in a solid image, uniformity can be achieved. Herein, the control of the ratio of the application quantity of the black ink to that of the color ink per area of the recording medium in the image forming region can be performed by, specifically, for example, when the application of the black ink and the color ink on the recording medium are performed by the ink-jet recording method, a method in which the number of pixels of the color ink to be adhered on the recording medium is controlled in the range of 10% to 100% of the number of pixels of the black ink to be adhered on the recording medium, a method in which the ejection quantity of the color ink is controlled to be smaller than the ejection quantity of the black ink, or a method in which the aforementioned methods are combined, so that the number of pixels of the color ink to be adhered on the recording medium is controlled to be in the range of 10% to 100% of the number of pixels of the color ink and the black ink to be adhered on the recording medium, and at that time, the ejection quantity of the color ink is controlled to be smaller than the ejection quantity of the black ink.

[0121] As the method for adhering the black ink and the color ink constituting the ink set for ink-jet recording according to the present embodiment, the ink-jet recording method is used in the present embodiment. As the ink-jet recording method, various publicly known conventional ink-jet methods, such as, for example, an ink-jet recording method using mechanical energy due to deformation of a piezoelectric element, can be used. However, in particular, it is preferable to use an ink-jet recording method using thermal energy, because remarkable effects of the present invention can be achieved.

[0122] That is, as described above, when the color ink including the polyvalent metal salt is used in order to improve

the prevention of color mixed bleeding between the black ink and the color ink, occurrence of kogation which occurs in the case where the image is formed by the ink-jet recording method using thermal energy in order to eject the color ink, and degradation of image quality accompanying this are effectively prevented by the ink-jet recording method according to the present embodiment using the ink set composed of the specified black ink (1) according to the present embodiment and the color ink (2). In conventional methods, when the color ink containing a polyvalent metal salt in order to prevent bleeding was repeatedly ejected from a recording head, sometimes, the outermost surface protection layer made of at least one of metals and metal oxides, such as tantalum and tantalum oxide, formed on a heater (heater element substrate), which applies thermal energy, is dissolved, and as a result, breaks in the heater occurred so as to cause a problem of incapability of ejection, and kogation was formed on a heater so as to cause a problem in that the image quality was affected. However, these problems are remedied by the present invention.

[0123] The ink-jet recording apparatus using thermal energy is as described in detail in the aforementioned first embodiment.

[0124] When a color image is formed by the ink-jet recording method according to the present embodiment, for example, a recording apparatus in which four recording heads as shown in Fig. 3 are arranged on a carriage is used. Fig. 12 shows an embodiment thereof. Recording heads 141, 142, 143, and 144 eject yellow ink (Y), magenta ink (M), cyan ink (C), and black ink (Bk), respectively. These heads are deployed in the aforementioned recording apparatus, and eject each of the inks responding to recording signals for ejection of each of the color inks, while, for example, a carriage is moved in the direction indicated by an arrow.

[0125] Fig. 12 shows an embodiment using four recording heads, although the present invention not limited to this number, and as shown in Fig. 13, it is also preferable to eject black ink 154, yellow ink 151, magenta ink 152, and cyan ink 153 from one recording head by separating liquid flow paths.

[0126] Two examples of specific arrangements of the ink-jet recording head appropriately used in the present embodiment are shown in Figs. 14 and 15. In Figs. 14 and 15, reference numerals 161 to 164 and 171 to 174, respectively, indicate recording heads for ejecting inks of yellow (Y), magenta (M), Cyan (C) and black (Bk), respectively. Each of the recording heads is arranged on the carriage in a manner similar to that as shown in Fig. 12, although the arrangements differ depending on the exact configurations. Each of the recording heads is deployed in the aforementioned recording apparatus, and ejects respective inks responding to a recording signal. Each of the recording heads moves with the carriage in the direction indicated by an arrow (1), and the recording medium moves with feed roller, etc., in the direction indicated by an arrow (2).

[0127] In the configuration example as shown in Fig. 14, recording heads Bk (164), C (163), M (162), and Y (161) are arranged in parallel on the carriage. The second configuration example, as shown in Fig. 15, is composed of a recording head for the black ink (174), and recording heads C (173), M (172), and Y (171) arranged in series with each other, and in parallel to the aforementioned recording head. The present invention may be applied to a so-called line printer having a configuration corresponding to that as shown in Fig. 14, in which a carrier is fixed and a recording medium is moved with a feed roller, etc., in the direction indicated by an arrow (2).

Examples

[0128] The present invention will be specifically explained using examples and comparative examples, although the present invention is not limited to the following examples. In the following description, parts and % are on a weight basis, unless otherwise specified.

Examples and Comparative Examples According to First Embodiment

Examples 1 to 33 and Comparative Examples 1 to 11

[0129] Each of liquid compositions and color inks were prepared using the following components. Regarding the preparation of the liquid composition and the color ink using a dye as a coloring material, the following components were dissolved, and thereafter, were pressure-filtrated using a microfilter having a pore size of 0.2 μm (manufactured by Fuji Photo Film Co., Ltd.) so as to produce each of the liquid compositions and the color inks.

[0130] Regarding the color inks using dyes as coloring materials, pigment dispersion liquids were produced by respective ways, and the resulting dispersion liquids were mixed with liquid media, etc. Thereafter, the resulting mixtures were pressure-filtrated using a microfilter having a pore size of 3 μm (manufactured by Fuji Photo Film Co., Ltd.) so as to produce respective pigment inks.

[0131] Liquid Compositions 1 to 4 were prepared from the following components. Liquid Composition 4 corresponded to the Comparative Example.

Liquid Composition 1	
Diethylene glycol	20 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	2 parts
Magnesium nitrate · 6 hydrates	2 parts
Taurine	2 parts
Water	74 parts

Liquid Composition 2	
Triethylene glycol monobutyl ether	10 parts
Glycerin	10 parts
Magnesium gluconate	4 parts
Taurine	3 parts
Water	73 parts

Liquid Composition 3	
Triethylene glycol monobutyl ether	10 parts
Glycerin	10 parts
Calcium glycerophosphate	1 part
Sodium aspartate	2 parts
Water	77 parts

Liquid Composition 4	
Diethylene glycol	20 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	2 parts
Water	78 parts

Black Ink 1

Production of Pigment Dispersion Liquid 1

[0132] 300 g of commercially available acidic carbon black "MA77" (pH of 3, manufactured by MITSUBISHI CHEMICAL CORPORATION) was sufficiently blended with 1,000 mL of water. Subsequently, 450 g of sodium hydrochlorite (effective chlorine concentration of 12%) was dropped thereto, and agitation was performed at 100°C to 105°C for 10 hours. The resulting slurry was filtrated with Toyo™ filter paper No. 2 (manufactured by Advantis Co.), and pigment particles were sufficiently washed with water. The resulting pigment wet cake was dispersed again in 3,000 mL of water, and was desalted with a reverse osmosis membrane until the electrical conductivity reached 0.2 μS. Furthermore, this pigment dispersion liquid (pH of 8 to 10) was concentrated to have a pigment concentration of 10% by weight. By the aforementioned method, -COONa group was introduced in the surface of the carbon black, so that Pigment Dispersion Liquid 1 including self-dispersion type carbon black was produced.

Preparation of Ink

[0133] The following components, including Pigment Dispersion Liquid 1 produced as described above, were mixed, and furthermore, were pressure-filtrated using a microfilter having a pore size of 3 μm (manufactured by Fuji Photo Film Co., Ltd.) so as to produce Black Ink 1.

The aforementioned Pigment Dispersion Liquid 1	40 parts
Glycerin	8 parts

(continued)

Trimethylolpropane	5 parts
Isopropyl alcohol	4 parts
Water	43 parts

Black Ink 2

Production of Pigment Dispersion Liquid 2

[0134]

Styrene-acrylic acid-butyl acrylate copolymer (acid value of 116, average molecular weight of 3,700)	5 parts
Triethanolamine	0.5 parts
Diethylene glycol	5 parts
Water	69.5 parts

[0135] The aforementioned components were mixed, and were heated to 70°C with a water bath so as to completely dissolve the resin component. 15 parts of carbon black "MA-100" (pH of 3.5, manufactured by MITSUBISHI CHEMICAL CORPORATION) and 5 parts of 2-propanol were added to the resulting solution, and premixing was performed for 30 minutes. Thereafter, dispersion treatment was performed under the following conditions.

dispersing machine: sand grinder (manufactured by Igarashi Kikai)

grinding media: zirconium beads of 1 mm in diameter

grinding media filling factor: 50% by volume

grinding time: 3 hours

[0136] Subsequently, centrifugal separation treatment was performed at 12,000 rpm for 20 minutes, so that coarse particles were removed and Pigment Dispersion Liquid 2 containing carbon black was produced.

Preparation of Ink

[0137] The following components, including Pigment Dispersion Liquid 2 produced as described above, were mixed, and furthermore, were pressure-filtrated using a microfilter having a pore size of 3 µm (manufactured by Fuji Photo Film Co., Ltd.) so as to produce Black Ink 2.

The aforementioned Pigment Dispersion Liquid 2	20 parts
Trimethylolpropane	5 parts
Diethylene glycol	10 parts
2-pyrrolidone	5 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	0.2 parts
Water	59.8 parts

Black Ink 3

[0138] The following components, including the aforementioned Example Compound 1 as a coloring material, were mixed, and furthermore, were pressure-filtrated using a microfilter having a pore size of 0.2 µm (manufactured by Fuji Photo Film Co., Ltd.) so as to produce Black Ink 3.

The aforementioned Example Compound 1 (in the formula, M designates NH ₄ ⁺)	2 parts
Diethylene glycol	10 parts
2-pyrrolidone	5 parts
2-propanol	5 parts
Sodium hydroxide	0.1 parts
Water	77.9 parts

Yellow Ink 1

Production of Pigment Dispersion Liquid 3

[0139]

Styrene-acrylic acid copolymer (acid value of 200, average molecular weight of 7,000)	5.5 parts
Monoethanolamine	1.0 part
Ion-exchanged water	67.5 parts
Diethylene glycol	5.0 parts

[0140] The aforementioned components were mixed, and were heated to 70°C with a water bath so as to completely dissolve the resin component. 20 parts of C.I. Pigment Yellow 93 and 1.0 part of isopropyl alcohol were added to the resulting solution, and premixing was performed for 30 minutes. Thereafter, dispersion treatment was performed under the following conditions.

dispersing machine: sand grinder
 grinding media: glass beads of 1 mm in diameter
 grinding media filling factor: 50% by volume
 grinding time: 3 hours

[0141] Subsequently, centrifugal separation treatment was performed at 12,000 rpm for 20 minutes, so that coarse particles were removed and Pigment Dispersion Liquid 3 was produced.

Preparation of Ink

[0142] The following components, including Pigment Dispersion Liquid 3 produced as described above, were mixed, and furthermore, were pressure-filtrated using a microfilter having a pore size of 3 µm (manufactured by Fuji Photo Film Co., Ltd.) so as to produce Yellow Ink 1.

The aforementioned Pigment Dispersion Liquid 3	20 parts
Glycerin	15 parts
Diethylene glycol	10 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	0.3 parts
Water	54.7 parts

Yellow Ink 2

[0143] The following components, including the aforementioned Example Compound 2 as a coloring material, were mixed and dissolved. Thereafter, pressure filtration was performed using a microfilter having a pore size of 0.2 µm (manufactured by Fuji Photo Film Co., Ltd.) so as to produce Yellow Ink 2.

The aforementioned Example Compound 2 (in the formula, M designates NH ₄ ⁺)	3 parts
Glycerin	7 parts
Diethylene glycol	5 parts
Urea	5 parts
Ethanol	2 parts
Water	88 parts

Magenta Ink 1

Production of Pigment Dispersion Liquid 4

[0144]

Styrene-acrylic acid copolymer (acid value of 200, average molecular weight of 7,000)	5.5 parts
Monoethanolamine	1.0 part
Ion-exchanged water	67.5 parts
Diethylene glycol	5.0 parts

[0145] The aforementioned components were mixed, and were heated to 70°C with a water bath so as to completely dissolve the resin component. 20 parts of C.I. Pigment Red 122 and 1.0 part of isopropyl alcohol were added to the resulting solution, and premixing was performed for 30 minutes. Thereafter, dispersion treatment was performed under the following conditions.

dispersing machine: sand grinder
 grinding media: glass beads of 1 mm in diameter
 grinding media filling factor: 50% by volume
 grinding time: 3 hours

[0146] Subsequently, centrifugal separation treatment was performed at 12,000 rpm for 20 minutes, so that coarse particles were removed and Pigment Dispersion Liquid 4 was produced.

Preparation of Ink

[0147] The following components, including Pigment Dispersion Liquid 4 produced as described above, were mixed, and furthermore, were pressure-filtrated using a microfilter having a pore size of 3 μm (manufactured by Fuji Photo Film Co., Ltd.) so as to produce Magenta Ink 1.

Pigment Dispersion Liquid 4	20 parts
Glycerin	15 parts
Diethylene glycol	10 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	0.3 parts
Water	54.7 parts

Magenta Ink 2

[0148] The following components, including the aforementioned Example Compound 3 as a coloring material, were mixed and dissolved. Thereafter, pressure filtration was performed using a microfilter having a pore size of 0.2 μm (manufactured by Fuji Photo Film Co., Ltd.) so as to produce Magenta Ink 2.

The aforementioned Example Compound 3 (in the formula, M designates NH_4^+)	3 parts
Glycerin	7 parts
Diethylene glycol	5 parts
Urea	5 parts
Ethanol	2 parts
Water	88 parts

Cyan Ink 1

Production of Pigment Dispersion Liquid 5

[0149]

Styrene-acrylic acid copolymer (acid value of 200, average molecular weight of 7,000)	5.5 parts
Monoethanolamine	1.0 part
Ion-exchanged water	67.5 parts
Diethylene glycol	5.0 parts

[0150] The aforementioned components were mixed, and were heated to 70°C with a water bath so as to completely dissolve the resin component. 20 parts of C.I. Pigment Blue 15:3 and 1.0 part of isopropyl alcohol were added to the resulting solution, and premixing was performed for 30 minutes. Thereafter, dispersion treatment was performed under the following conditions.

dispersing machine: sand grinder
 grinding media: glass beads of 1 mm in diameter
 grinding media filling factor: 50% by volume
 grinding time: 3 hours

[0151] Subsequently, centrifugal separation treatment was performed at 12,000 rpm for 20 minutes, so that coarse particles were removed and Pigment Dispersion Liquid 5 was produced.

Preparation of Ink

[0152] The following components, including Pigment Dispersion Liquid 5 produced as described above, were mixed, and furthermore, were pressure-filtrated using a microfilter having a pore size of 3 µm (manufactured by Fuji Photo Film Co., Ltd.) so as to produce Cyan Ink 1.

Pigment Dispersion Liquid 5	20 parts
Glycerin	15 parts
Diethylene glycol	10 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	0.3 parts
Water	54.7 parts

Cyan Ink 2

[0153] The following components, including the aforementioned Example Compound 4 as a coloring material, were mixed and dissolved. Thereafter, pressure filtration was performed using a microfilter having a pore size of 0.2 µm (manufactured by Fuji Photo Film Co., Ltd.) so as to produce Cyan Ink 2.

The aforementioned Example Compound 4 (in the formula, M designates NH ₄ ⁺)	3 parts
Glycerin	7 parts
Diethylene glycol	5 parts
Urea	5 parts
Ethanol	2 parts
Water	88 parts

Evaluation and Evaluation Criteria

Evaluation Test

[0154] Evaluation tests will be described below.

Evaluation 1

[0155] Liquid Compositions 1 to 3 having configurations according to the present invention and Liquid Composition 4 of the Comparative Example produced as described above were evaluated by ejecting the liquid compositions using an ink-jet recording apparatus including an on-demand type multi-recording head BC-02 (manufactured by CANON KABUSHIKI KAISHA, and an outermost surface protection layer on a heater is made of tantalum and tantalum oxide), which ejects liquid compositions by applying thermal energy to inks responding to a recording signal, under the following condition. Regarding the liquid composition ejection condition of the aforementioned ink-jet recording apparatus, V_{th} (a critical voltage required for ejection at a minimum level) was measured with a pulse width of $1.1 \mu s$ (On) + $3.0 \mu s$ (Off) + $3.2 \mu s$ (On) and driving frequency of 6,250 Hz, and thereafter, the liquid composition was ejected applying V_{op} (driving voltage) which corresponds to r value of 1.6. Ejection durability and occurrence status of kogation adhesion were evaluated based on the following method and criteria. The results thereof are as shown in Table 1.

1. Ejection durability

[0156] Continuous ejection was performed with the aforementioned apparatus and conditions, and droplets ejected from the recording head were collected into a container at intervals of 1×10^6 times of ejection, and were weighed with an electrobalance. An average ejection droplet quantity of 1×10^6 times of ejection was calculated from increase in weight of the container. The continuous ejection was performed until 1×10^8 times, and evaluation was performed based on the following criteria.

A: the average ejection droplet quantity of 9.9×10^7 times to 1×10^8 times was 90% or more of the average ejection droplet quantity of 0 to 1×10^6 times.

B: the average ejection droplet quantity of 9.9×10^7 times to 1×10^8 times was less than 90%, but 70% or more of the average ejection droplet quantity of 0 to 1×10^6 times.

C: the average ejection droplet quantity of 9.9×10^7 times to 1×10^8 times was less than 70% of the average ejection droplet quantity of 0 to 1×10^6 times.

D: ejection became impossible during the continuous ejection.

2. Quantity of kogation adhesion

[0157] The recording head, on which the aforementioned evaluation of ejection durability of head was completed, was disassembled, and the surface of the heater of the nozzle used for the ejection durability test was visually inspected with an optical microscope (magnification of 400 times) so as to determine the quantity of kogation adhesion and to evaluate the quantity of kogation adhesion based on the following criteria.

A: kogation adhesion was hardly observed.

B: kogation adhesion was observed to some degree.

C: kogation adhesion was observed to a large degree.

D: kogation adhesion was observed to very large degree.

Table 1

		1. Ejection Durability	2. Kogation Adhesion Quantity
Example 1	Liquid Composition 1	A	A
Example 2	Liquid Composition 2	A	A
Example 3	Liquid Composition 3	A	A
Comparative Example 1	Liquid Composition 4	A	A

Evaluation 2

[0158] Recording was performed on a recording paper using each of the color inks and each of Liquid Compositions 1 to 3 prepared as described above in combinations as shown in Table 2. As the ink-jet recording apparatus, a recording apparatus having a configuration similar to that as shown in Fig. 4 was used, and an image was formed using two

recording heads among the five recording heads as shown in Fig. 7. At this time, the liquid composition was under picked so as to adhere on the recording paper, and subsequently, the color ink was adhered. The position of the adhesion of the liquid composition on the recording paper and the position of the adhesion of the color ink on the recording paper were controlled to precisely coincide with each other. The recording head used for this recording had a record density of 360 dpi, and the driving frequency was specified to be 5 kHz. The ejection volume per dot of the head used for the color ink was 80 pl/dot, and that of the head used for the liquid composition was 40 pl/dot. As the recording paper, a paper manufactured by CANON KABUSHIKI KAISHA, (trade name: PB paper) and a paper manufactured by Xerox Corporation, (trade name: 4024 paper) were used.

3. Water Resistance of Image

[0159] Printing was performed using each of the color inks and each of the liquid compositions in combinations as shown in Table 2 by the aforementioned method. The print was stood for 1 hour, and thereafter, print density was measured with a Macbeth RD915 (trade name, manufactured by Macbeth). Subsequently, this print was immersed for 3 minutes in a container filled with tap water, was removed, and dried. Then, the print density was measured again, and the density retention rate of the print was determined so as to evaluate water resistance. The density retention rate is preferably 95% or more in practice. The results of the evaluation are shown in Table 2. The evaluation criteria were as described below.

$$\text{print density retention rate} = \left(\frac{\text{print density after immersion in water}}{\text{print density before immersion in water}} \right) \times 100$$

A: print density retention rate is 95% or more.

B: print density retention rate is 85% or more, but 95% or less.

C: print density retention rate is less than 85%.

4. Print Quality of Image (Bleeding)

[0160] Printing of alphanumeric characters (12 points) was performed in a manner similar to that as described above, and after standing for 1 hour, sharpness of the characters and degree of whisker-like bleeding generated from the characters were evaluated based on a visual inspection. The results of the evaluation are shown in Table 2. The evaluation criteria were as described below.

A: character has sharpness and whisker-like bleeding was not observed.

B: character does not have sharpness and bleeding was observed to some degree.

C: character does not have sharpness and bleeding was observed to a great degree.

Table 2

	Combination Used For Ink-Jet Recording		3. Water Resistance		4. Print Quality	
	Liquid Composition	Colored Ink	PB Paper	4024 Paper	PB Paper	4024 Paper
Example 4	Liquid Composition 1	Black 1 (self-dispersion pigment)	A	A	A	A
Example 5	Liquid Composition 1	Black 2 (pigment)	A	A	A	A
Example 6	Liquid Composition 1	Black 3 (dye)	A	A	A	A

Table 2 (continued)

	Combination Used For Ink-Jet Recording		3. Water Resistance		4. Print Quality	
	Liquid Composition	Colored Ink	PB Paper	4024 Paper	PB Paper	4024 Paper
5	Example 7	Liquid Composition 1	Yellow 1 (pigment)	A	A	A
10	Example 8	Liquid Composition 1	Yellow 2 (dye)	A	A	A
	Example 9	Liquid Composition 1	Magenta 1 (pigment)	A	A	A
15	Example 10	Liquid Composition 1	Magenta 2 (dye)	A	A	A
	Example 11	Liquid Composition 1	Cyan 1 (pigment)	A	A	A
20	Example 12	Liquid Composition 1	Cyan 2 (dye)	A	A	A
	Example 13	Liquid Composition 2	Black 1 (self-dispersion pigment)	A	A	A
25	Example 14	Liquid Composition 2	Black 2 (pigment)	A	A	A
	Example 15	Liquid Composition 2	Black 3 (dye)	A	A	A
30	Example 16	Liquid Composition 2	Yellow 1 (pigment)	A	A	A
	Example 17	Liquid Composition 2	Yellow 2 (dye)	A	A	A
35	Example 18	Liquid Composition 2	Magenta 1 (pigment)	A	A	A
	Example 19	Liquid Composition 2	Magenta 2 (dye)	A	A	A
40	Example 20	Liquid Composition 2	Cyan 1 (pigment)	A	A	A
	Example 21	Liquid Composition 2	Cyan 2 (dye)	A	A	A
45	Example 22	Liquid Composition 3	Black 1 (self-dispersion pigment)	A	A	A
	Example 23	Liquid Composition 3	Black 2 (pigment)	A	A	A
50	Example 24	Liquid Composition 3	Black 3 (dye)	A	A	A
	Example 25	Liquid Composition 3	Yellow 1 (pigment)	A	A	A
55	Example 26	Liquid Composition 3	Yellow 2 (dye)	A	A	A

Table 2 (continued)

	Combination Used For Ink-Jet Recording		3. Water Resistance		4. Print Quality	
	Liquid Composition	Colored Ink	PB Paper	4024 Paper	PB Paper	4024 Paper
5	Example 27	Liquid Composition 3	Magenta 1 (pigment)	A	A	A
10	Example 28	Liquid Composition 3	Magenta 2 (dye)	A	A	A
	Example 29	Liquid Composition 3	Cyan 1 (pigment)	A	A	A
15	Example 30	Liquid Composition 3	Cyan 2 (dye)	A	A	A
	Comparative Example 2	Liquid Composition 4	Black 1 (self-dispersion pigment)	A	A	B
20	Comparative Example 3	Liquid Composition 4	Black 2 (pigment)	A	A	B
	Comparative Example 4	Liquid Composition 4	Black 3 (dye)	C	C	C
25	Comparative Example 5	Liquid Composition 4	Yellow 1 (pigment)	A	A	B
	Comparative Example 6	Liquid Composition 4	Yellow 2 (dye)	B	B	C
30	Comparative Example 7	Liquid Composition 4	Magenta 1 (pigment)	A	A	B
	Comparative Example 8	Liquid Composition 4	Magenta 2 (dye)	C	C	C
35	Comparative Example 9	Liquid Composition 4	Cyan 1 (pigment)	A	A	B
	Comparative Example 10	Liquid Composition 4	Cyan 2 (dye)	C	C	C

5. Bleeding (color mixed bleeding between different colors)

[0161] An ink set composed of a liquid composition and color inks in each of combinations as shown in Table 3 was used. The aforementioned two kinds of plain papers were printed with solid patches of the liquid composition, and immediately after that, the papers were printed with solid patches of the black ink on the region of the solid patches of the liquid composition. Furthermore, immediately after that, the papers were printed with solid patches of each of yellow, magenta, and cyan inks on the region of the solid patches of the liquid composition adjacently to the solid patches of the black ink. The boundary portions of the resulting solid patch prints were visually inspected so as to evaluate bleeding between the black ink and each of the color inks. The evaluation criteria were as described below.

A: Bleeding is not observed at all boundaries.

B: Bleedings are observed to some degree, but those are not obtrusive.

C: Bleedings are observed to a large degree at almost every boundary.

[0162] The results of the evaluation are shown in Table 3.

Table 3

	Ink Set					5. Bleeding	
	Liquid Composition	Black Ink	Color Ink			PB Paper	4024 Paper
Example 31	Liquid Composition 1	Black 1 (self-dispersion pigment)	Yellow 1 (pigment)	Magenta 1 (pigment)	Cyan 1 (pigment)	A	A
Example 32	Liquid Composition 1	Black 3 (dye)	Yellow 2 (dye)	Magenta 2 (dye)	Cyan 2 (dye)	A	A
Example 33	Liquid Composition 2	Black 1 (self-dispersion pigment)	Yellow 1 (pigment)	Magenta 1 (pigment)	Cyan 1 (pigment)	A	A
Example 34	Liquid Composition 2	Black 3 (dye)	Yellow 2 (dye)	Magenta 2 (dye)	Cyan 2 (dye)	A	A
Example 35	Liquid Composition 3	Black 1 (self-dispersion pigment)	Yellow 1 (pigment)	Magenta 1 (pigment)	Cyan 1 (pigment)	A	A
Example 36	Liquid Composition 3	Black 3 (dye)	Yellow 2 (dye)	Magenta 2 (dye)	Cyan 2 (dye)	A	A
Comparative Example 11	Liquid Composition 4	Black 1 (self-dispersion pigment)	Yellow 1 (pigment)	Magenta 1 (pigment)	Cyan 1 (pigment)	C	C
Comparative Example 12	Liquid Composition 4	Black 3 (dye)	Yellow 2 (dye)	Magenta 2 (dye)	Cyan 2 (dye)	C	C

Examples and Comparative Example According to Second Embodiment

Examples 37 to 39 and Comparative Example 13

[0163] Ink sets of Examples 37 to 39 and Comparative Example 13 were produced by the combination of the black ink and the color inks of yellow, magenta, and cyan. Each of the inks was produced by the following methods using the components as described below. The black ink constituting each of the ink set was prepared by blending the aforementioned Pigment Dispersion Liquid 1 or 2 with the components as described below, and subsequently, by pressure-filtrating the resulting mixture using a microfilter having a pore size of 3 μm (manufactured by Fuji Photo Film Co., Ltd.). Each of the color ink which includes a dye, and constitutes each of ink sets, was prepared by blending the components as described below, and subsequently, by pressure-filtrating the resulting mixture using a microfilter having a pore size of 0.2 μm (manufactured by Fuji Photo Film Co., Ltd.). Primary compositions of the ink sets of Examples 37 to 39 and Comparative Example 13 are as shown in Table 4.

Ink Set of Example 37

[0164]

5

Black Ink Composition	
The aforementioned Pigment Dispersion Liquid 1	40 parts
Glycerin	8 parts
Trimethylolpropane	5 parts
Isopropyl alcohol	4 parts
Water	43 parts

10

15

Yellow Ink Composition	
C.I. Acid Yellow 23	2.5 parts
Glycerin	5 parts
Diethylene glycol	5 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	1 part
Magnesium acetate · 4 hydrates	2 parts
Taurine	1 part
Water	83.5 parts

20

25

Magenta Ink Composition	
C.I. Acid Red 289	2 parts
Glycerin	8 parts
Diethylene glycol	5 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	1 part
Magnesium nitrate · 6 hydrates	1 parts
Sodium aspartate	0.5 parts
Water	82.5 parts

30

35

40

45

Cyan Ink Composition	
C.I. Acid Blue 9	2 parts
Glycerin	8 parts
Diethylene glycol	5 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	1 part
Magnesium nitrate · 6 hydrates	1 part
Taurine	1 part
Water	82 parts

Ink Set of Example 38

[0165]

50

Black Ink Composition	
The aforementioned Pigment Dispersion Liquid 1	40 parts
Glycerin	5 parts
Diethylene glycol	5 parts
2-pyrrolidone	5 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	0.3 parts

55

EP 1 191 077 A1

(continued)

Black Ink Composition	
Water	44.7 parts

Yellow Ink Composition	
C.I. Acid Yellow 23	2.5 parts
Glycerin	5 parts
Diethylene glycol	5 parts
Trimethylolpropane	5 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	1 part
Magnesium gluconate	1 part
Taurine	1 part
Water	79.5 parts

Magenta Ink Composition	
C.I. Acid Red 289	2 parts
Glycerin	8 parts
Diethylene glycol	5 parts
Thiodiglycol	5 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	1 part
Magnesium gluconate	1.5 parts
Taurine	1 part
Water	76.5 parts

Cyan Ink Composition	
C.I. Acid Blue 9	2 parts
Ethylene glycol	8 parts
Diethylene glycol	5 parts
Trimethylolpropane	5 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	1 part
Calcium gluconate	1 part
Taurine	1 part
Water	77 parts

Ink Set of Example 39

[0166]

Black Ink Composition	
The aforementioned Pigment Dispersion Liquid 2	20 parts
Trimethylolpropane	5 parts
Diethylene glycol	10 parts
2-pyrrolidone	5 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	0.2 parts
Water	59.8 parts

Yellow Ink Composition		
5	C.I. Acid Yellow 23	2.5 parts
	Glycerin	5 parts
	Diethylene glycol	5 parts
	Trimethylolpropane	5 parts
	Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	1 part
10	Calcium glycerophosphate	1 part
	Taurine	1 part
	Water	79.5 parts

Magenta Ink Composition		
15	C.I. Acid Red 289	2 parts
	Glycerin	8 parts
	Diethylene glycol	5 parts
	Thiodiglycol	5 parts
	Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	1 part
20	Calcium glycerophosphate	1 part
	Taurine	1 part
	Water	77 parts

Cyan Ink Composition		
30	C.I. Acid Blue 9	2 parts
	Ethylene glycol	8 parts
	Diethylene glycol	5 parts
	Trimethylolpropane	5 parts
	Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	1 part
35	Calcium glycerophosphate	1 part
	Taurine	1 part
	Water	84.5 parts

Ink Set of Comparative Example 13

[0167]

Black Ink Composition		
45	The aforementioned Pigment Dispersion Liquid 1	40 parts
	Glycerin	8 parts
	Trimethylolpropane	5 parts
	Isopropyl alcohol	4 parts
	Water	43 parts

Yellow Ink Composition		
55	C.I. Acid Yellow 23	2.5 parts
	Glycerin	5 parts
	Diethylene glycol	5 parts
	Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	1 part
	Water	86.5 parts

Magenta Ink Composition	
C.I. Acid Red 289	2 parts
Glycerin	8 parts
Diethylene glycol	5 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals CO., Ltd.)	1 part
Water	84 parts

Cyan Ink Composition	
C.I. Acid Blue 9	2 parts
Glycerin	8 parts
Diethylene glycol	5 parts
Acetylenol EH (manufactured by Kawaken Fine Chemicals Co., Ltd.)	1 part
Water	84 parts

Table 4

Primary Composition of Ink Set				
Ink Set	Kind of Ink	Coloring Material	Polyvalent Metal Salt	Acid Including Amino Group
Example 37	Black	Dispersion Liquid 1	-	-
	Yellow	Acid Y-23	Magnesium acetate	Taurine
	Magenta	Acid R-289	Magnesium nitrate	Aspartic acid
	Cyan	Acid B-9	Magnesium acetate	Taurine
Example 38	Black	Dispersion Liquid 1	-	-
	Yellow	Acid Y-23	Magnesium gluconate	Taurine
	Magenta	Acid R-289	Magnesium gluconate	Taurine
	Cyan	Acid B-9	Calcium gluconate	Taurine
Example 39	Black	Dispersion Liquid 2	-	-
	Yellow	Acid Y-23	Calcium glycerophosphate	Taurine
	Magenta	Acid R-289	Calcium glycerophosphate	Taurine
	Cyan	Acid B-9	Calcium glycerophosphate	Taurine
Comparative Example 13	Black	Dispersion Liquid 1	-	-
	Yellow	Acid Y-23	-	-
	Magenta	Acid R-289	-	-
	Cyan	Acid B-9	-	-

Evaluation Test

[0168] Evaluation tests will be described below.

Evaluation 1

[0169] Evaluation was performed by ejecting the inks of the ink set of the aforementioned Examples 37 to 39 and Comparative Example 13 using an ink-jet recording apparatus including an on-demand type multi-recording head BC-02 (manufactured by CANON KABUSHIKI KAISHA, and an outermost surface protection layer on a heater is made of tantalum and tantalum oxide), which ejects inks by applying thermal energy to inks responding to a recording signal, under the following condition. Regarding the ink ejection condition of the aforementioned ink-jet recording apparatus, V_{th} (a critical voltage required for ejection at a minimum level) was measured with a pulse width of $1.1 \mu s$ (On) + $3.0 \mu s$ (Off) + $3.2 \mu s$ (On) and driving frequency of 6,250 Hz, and thereafter, the ink was ejected applying V_{op} (driving voltage) which corresponds to r value of 1.6. Ejection durability and occurrence status of kogation adhesion to the heater of the ink-jet recording head when ink-jet recording were performed under the aforementioned condition were evaluated based on the following method and criteria. The results thereof are as shown in Fig. 5.

1. Ejection durability

[0170] Continuous ejection was performed with the aforementioned apparatus and conditions, and droplets ejected from the recording head were collected into a container at intervals of 1×10^6 times of ejection, and were weighed with an electrobalance. An average ejection droplet quantity of 1×10^6 times of ejection was calculated from increase in weight of the container. The continuous ejection was performed until 1×10^8 times, and evaluation was performed based on the following criteria.

A: the average ejection droplet quantity of 9.9×10^7 times to 1×10^8 times was 90% or more of the average ejection droplet quantity of 0 to 1×10^6 times.

B: the average ejection droplet quantity of 9.9×10^7 times to 1×10^8 times was less than 90%, but 70% or more of the average ejection droplet quantity of 0 to 1×10^6 times.

C: the average ejection droplet quantity of 9.9×10^7 times to 1×10^8 times was less than 70% of the average ejection droplet quantity of 0 to 1×10^6 times.

D: ejection became impossible during the continuous ejection.

2. Quantity of kogation adhesion

[0171] The recording head, on which the aforementioned evaluation of ejection durability of head was completed, was disassembled, and the surface of the heater of the nozzle used for the ejection durability test was visually inspected with an optical microscope (magnification of 400 times) so as to evaluate the quantity of kogation adhesion based on the following criteria.

A: kogation adhesion was hardly observed.

B: kogation adhesion was observed to some degree.

C: kogation adhesion was observed to a large degree.

D: kogation adhesion was observed to a very large degree.

Table 5

Ink Set	Kind of Ink	1. Ejection Durability	2. Kogation Adhesion Quantity
Example 37	Black	A	B
	Yellow	A	B
	Magenta	A	B
	Cyan	A	B
Example 38	Black	A	B
	Yellow	A	B
	Magenta	A	B
	Cyan	A	B

Table 5 (continued)

Ink Set	Kind of Ink	1. Ejection Durability	2. Kogation Adhesion Quantity
Example 39	Black	A	B
	Yellow	A	B
	Magenta	A	B
	Cyan	A	B
Comparative Example 13	Black	A	B
	Yellow	A	B
	Magenta	A	B
	Cyan	A	B

Evaluation 2

Examples 37 to 42 and Comparative Examples 13 and 14

[0172] Each of the inks of the ink sets of Examples 37 to 39 according to the present invention and Comparative Example 13 was mounted on a color ink-jet printer (BJC-700J, manufactured by CANON KABUSHIKI KAISHA), that is, an ink-jet recording apparatus including an on-demand type multi-recording head, which ejects inks by applying thermal energy to the inks responding to a recording signal. Subsequently, evaluation regarding the following items 3 and 4 were performed.

[0173] Images were produced using Examples 37 to 39 according to the present invention and Comparative Example 13 by applying the black ink and the color ink at the same position on the recording medium wherein the application of the color ink is prior to the application of the black ink (under pick). The ink-jet recordings by the under pick method using the ink sets of Examples 37 to 39 were taken as Examples 40 to 42, respectively, and the ink-jet recording by the under pick method using the ink set of Comparative Example 13 was taken as Comparative Examples 14. The evaluation thereof was performed in a manner similar to that as described above. Regarding the ratio of the application quantity of the black ink to that of the color ink per area of the recording medium, the ratio of the black ink to the color ink was specified to be 10 : 2.5, and regarding the ratio among the color inks, the ratio of yellow ink to magenta ink to cyan ink was specified to be 1 : 1 : 1. As the paper for the evaluation test, two kinds of plain paper, a copying paper manufactured by CANON KABUSHIKI KAISHA (trade name: PB PAPER) and a copying paper manufactured by Xerox Corporation (trade name: 4024 PAPER), were used. The results thereof are as shown in Table 6.

3. Bleeding between Black Ink and Color Ink

[0174] The aforementioned two kinds of plain papers were printed with solid patches of the black ink in each of the ink sets, and immediately after that, the papers were printed with solid patches of each of yellow, magenta, and cyan color inks adjacently to the solid patches of the black ink. The boundary portions of the resulting solid patch prints were visually inspected so as to evaluate bleeding between the black ink and the color inks. The evaluation criteria were as described below.

A: Bleeding is not observed at all boundaries.

B: Bleedings are observed to some degree.

C: Bleedings are observed to a large degree at almost every boundary.

4. Density of Black Ink Portion at Adjacent Boundary Portions between Black Ink and Color Ink (Occurrence of White Haze)

[0175] The aforementioned two kinds of plain papers were printed with solid patches of the black ink in each of the ink sets, and immediately after that, the papers were printed with solid patches of each of yellow, magenta, and cyan inks adjacently to the solid patches of the black ink. The occurrence of white haze at the adjacent boundary portions between the black ink and the color inks were visually inspected so as to evaluate. The evaluation criteria were as described below.

A: Reduction of density is not observed in the boundary portion, and white haze does not occur.

B: Reduction of density is observed in the boundary portion, and occurrence of white haze is observed, although these do not cause any problem in practice.

C: Reduction of density is observed to a large degree in the boundary portion, and occurrence of white haze is observed to a large degree.

Table 6

	Under Pick	3. Bleeding between Black Ink and Color Ink		4. White haze between Black Ink and Color Ink	
		PB paper	XX paper	PB paper	XX paper
Example 37	Not Performed	A	A	B	B
Example 38	Not Performed	A	A	B	B
Example 39	Not Performed	A	A	B	B
Example 40	Performed	A	A	A	A
Example 41	Performed	A	A	A	A
Example 42	Performed	A	A	A	A
Comparative Example 13	Not Performed	C	C	C	C
Comparative Example 14	Performed	C	C	B	B

[0176] In Table 6, the term PB paper represents the copying paper manufactured by CANON KABUSHIKI KAISHA (trade name: PB PAPER), and the term XX paper represents the copying paper manufactured by Xerox Corporation (trade name: 4024 PAPER).

[0177] As described above, according to the present invention, the liquid composition, which has water resistance and excellent print quality, and can reduce color bleeding that occurs in formation of color images, and furthermore, which can achieve long-life ink-jet recording heads, as well as the ink for ink-jet, the ink set for ink-jet recording, the ink-jet recording method, the recording unit, the ink cartridge, and the ink-jet recording apparatus are provided.

[0178] While the present invention has been described with reference to what are presently considered to be the preferred embodiments, it is to be understood that the invention is not limited to the disclosed embodiments. On the contrary, the invention is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended Claims. The scope of the following Claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

[0179] A liquid composition for ink-jet recording, or an ink set for ink-jet recording which produces an image having water resistance and excellent print quality, and which can reduce color bleeding that occurs in formation of color images, and furthermore, which can extend a life-span of ink-jet recording heads, as well as an ink-jet recording method, a recording unit, an ink cartridge and an ink-jet recording apparatus are provided. The liquid composition or a color ink constituting the ink set comprising a polyvalent metal salt, a material selected from the group consisting of acids including amino groups and salts thereof, and a liquid medium is used.

Claims

1. A liquid composition for ink-jet recording, which is used together with a color ink and reacts with the color ink when it comes into contact with the color ink, the liquid composition comprising:

- (a) a polyvalent metal salt;
- (b) a material selected from the group consisting of acids including amino groups and salts thereof; and
- (c) a liquid medium.

2. The liquid composition according to Claim 1, wherein the total content of said polyvalent metal salts is 0.005% to 20% by weight relative to the total quantity of said liquid composition, and the total content of said materials selected

from the group consisting of acids including amino groups and salts thereof is 0.005% to 20% by weight relative to the total quantity of said liquid composition.

5 3. The liquid composition according to Claim 1 or 2, wherein said polyvalent metal salt is at least one selected from the group consisting of polyvalent metal salts of nitric acid, hydroxycarboxylic acid, and polyol phosphate.

4. The liquid composition according to Claim 3, wherein said polyvalent metal salt of nitric acid, hydroxycarboxylic acid, or polyol phosphate is at least one selected from the group consisting of magnesium nitrate, calcium nitrate, barium nitrate, iron(II) nitrate, copper(II) nitrate, zinc nitrate, magnesium acetate, calcium acetate, barium acetate, iron(II) acetate, copper(II) acetate, zinc acetate, magnesium gluconate, calcium gluconate, barium gluconate, iron(II) gluconate, copper(II) gluconate, zinc gluconate, magnesium glycerophosphate, and calcium glycerophosphate.

10 5. The liquid composition according to any one of Claims 1 to 4, wherein the group consisting of acids including amino groups and salts thereof is at least one selected from the group consisting of amidosulfuric acid (sometimes called sulfamic acid), aminomethanesulfonic acid, taurine (sometimes called 2-aminoethanesulfonic acid), carbamic acid, glycine, alanine, β -alanine, aspartic acid, and glutamic acid.

15 6. An ink-jet recording method comprising the steps of:

20 (i) ejecting each of said liquid composition according to any one of Claims 1 to 5 and said color ink toward a recording medium by applying energy to said liquid composition and said color ink; and
(ii) forming a state of contact between said liquid composition and said color ink on the recording medium.

25 7. The ink-jet recording method according to Claim 6, wherein a coloring material of said color ink is a pigment.

8. The ink-jet recording method according to Claim 6, wherein a coloring material of said color ink is a dye including at least one carboxylic group.

30 9. The ink-jet recording method according to any one of Claims 6 to 8, wherein said energy is thermal energy.

10. The ink-jet recording method according to any one of Claims 6 to 9, wherein application of said liquid composition on a recording medium is performed prior to application of said color ink on the recording medium.

35 11. The ink-jet recording method according to any one of Claims 6 to 9, wherein application of said liquid composition on a recording medium is performed after application of said color ink on the recording medium.

40 12. The ink-jet recording method according to any one of Claims 6 to 9, wherein application of said liquid composition on a recording medium is performed after application of said color ink on the recording medium, and subsequently, said color ink is further applied on the recording medium.

13. The ink-jet recording method according to any one of Claims 6 to 9, wherein application of said color ink on a recording medium is performed after application of said liquid composition on the recording medium, and subsequently, said liquid composition is further applied on the recording medium.

45 14. The ink-jet recording method according to any one of Claims 6 to 9, wherein the liquid composition and the color ink mix with each other immediately after their ejection from an ink-jet recording apparatus toward the recording medium and the mixture is applied on a recording medium.

50 15. An ink set for ink-jet recording comprising:

(1) a liquid composition according to any one of Claims 1 to 5; and
(2) a color ink which includes a coloring material and a liquid medium, and reacts with said liquid composition due to contact therebetween.

55 16. A recording unit comprising:

a liquid composition container portion containing a liquid composition according to any one of Claims 1 to 5;
an ink container portion containing a color ink which reacts with said liquid composition due to contact there-

between; and

an ink-jet recording head that ejects each of said liquid composition and said color ink by applying energy to said liquid composition and said color ink.

17. The recording unit according to Claim 16, wherein said ink-jet recording head is provided with a heater having an outermost surface protection layer containing a material selected from the group consisting of metals and metal oxides.

18. The recording unit according to Claim 17, wherein tantalum or tantalum oxide is contained as said material selected from the group consisting of metals and metal oxides.

19. An ink cartridge comprising:

a liquid composition container portion containing a liquid composition according to any one of Claims 1 to 5; and an ink container portion containing a color ink which includes a coloring material and a liquid medium, and reacts with said liquid composition due to contact therebetween.

20. An ink-jet recording apparatus comprising:

a liquid composition container portion containing a liquid composition;
a color ink container portion containing a color ink which reacts with said liquid composition due to contact therebetween; and
an ink-jet recording head that ejects each of said liquid composition and said color ink by applying energy to said liquid composition and said color ink,

wherein said liquid composition is a liquid composition according to any one of Claims 1 to 5.

21. The ink-jet recording apparatus according to Claim 20, wherein said ink-jet recording head is provided with a heater having an outermost surface protection layer containing a material selected from the group consisting of metals and metal oxides, and said ink-jet recording apparatus is provided with a device for applying an electrical pulse signal to said heater responding to recording information.

22. The ink-jet recording apparatus according to Claim 21, wherein tantalum or tantalum oxide is contained as said material selected from the group consisting of metals and metal oxides.

23. The ink-jet recording apparatus according to any one of Claims 20 to 22, wherein the ratio of an energy E_{op} , which is input into a heater in order to eject a liquid composition, to the minimum input energy E_{th} , which is necessary for the heater to eject said liquid composition from a recording head, E_{op}/E_{th} , satisfies the following relationship,

$$1.10 \leq E_{op}/E_{th} \leq 1.90.$$

24. An ink set for ink-jet recording comprising:

(1) a color ink including a coloring material, a liquid medium, a polyvalent metal salt, and a material selected from the group consisting of acids including amino groups and salts thereof; and
(2) black ink which includes a coloring material and a liquid medium, and reacts with the color ink by contact with the color ink.

25. The ink set for ink-jet recording according to Claim 24, wherein the total content of said polyvalent metal salts included in said color ink is 0.005% to 20% by weight relative to the total quantity of said color ink, and the total content of said materials selected from the group consisting of acids including amino groups and salts thereof is 0.005% to 20% by weight relative to the total quantity of said color ink.

26. The ink set for ink-jet recording according to Claim 24 or 25, wherein said polyvalent metal salt is at least one selected from the group consisting of polyvalent metal salts of nitric acid, acetic acid, hydroxycarboxylic acid, and polyol phosphate.

27. The ink set for ink-jet recording according to Claim 26, wherein said polyvalent metal salt of nitric acid, acetic acid, hydroxycarboxylic acid, or polyol phosphate is at least one selected from the group consisting of magnesium nitrate, calcium nitrate, barium nitrate, iron(II) nitrate, copper(II) nitrate, zinc nitrate, magnesium acetate, calcium acetate, barium acetate, iron(II) acetate, copper(II) acetate, zinc acetate, magnesium gluconate, calcium gluconate, barium gluconate, iron(II) gluconate, copper(II) gluconate, zinc gluconate, magnesium glycerophosphate, and calcium glycerophosphate.
28. The ink set for ink-jet recording according to any one of Claims 24 to 27, wherein the group consisting of acids including amino groups and salts thereof is at least one selected from the group consisting of amidosulfuric acid (sometimes called sulfamic acid), aminomethanesulfonic acid, taurine (sometimes called 2-aminoethanesulfonic acid), carbamic acid, glycine, alanine, β -alanine, aspartic acid, and glutamic acid.
29. The ink set for ink-jet recording according to any one of Claims 24 to 28, wherein a coloring material of said black ink is at least one selected from the group consisting of carbon black and pigments.
30. The ink set for ink-jet recording according to any one of Claims 24 to 28, wherein a coloring material of said black ink is a dye including at least one carboxylic group.
31. The ink set for ink-jet recording according to any one of Claims 24 to 30, wherein the water contents in each of said black ink and said color ink is 35% to 96% by mass based on the total amount of said respective inks.
32. The ink set for ink-jet recording according to any one of Claims 24 to 31, wherein said color ink is at least one ink selected from the group consisting of yellow ink, magenta ink, and cyan ink.
33. The ink set for ink-jet recording according to any one of Claims 24 to 32, which is used for an ink-jet printer provided with a recording head comprising:
- a heater applying thermal energy to an ink in order to eject said ink from an orifice; and
 - an outermost surface protection layer containing a material selected from the group consisting of metals and metal oxides in order to protect said heater.
34. The ink set for ink-jet recording according to Claim 33, wherein tantalum or tantalum oxide is contained as said material selected from the group consisting of metals and metal oxides.
35. An ink-jet recording method comprising the steps of:
- (i) ejecting each of said black ink and said color ink included in an ink set according to any one of Claims 24 to 34 toward a recording medium by applying energy to said black ink and said color ink; and
 - (ii) forming a state of contact between said black ink and said color ink on the recording medium.
36. The ink-jet recording method according to Claim 35, wherein said black ink and said color ink are applied to a recording medium so as to overlap each other on the recording medium, and application of said color ink is performed prior to the application of said black ink.
37. The ink-jet recording method according to Claim 35 or 36, wherein said energy is thermal energy.
38. A recording unit comprising:
- ink container portions containing each of said inks constituting an ink set according to any one of Claims 24 to 34; and
 - an ink-jet recording head for ejecting each of the inks supplied from said ink container portions by applying energy to said inks.
39. The recording unit according to Claim 38, wherein said ink-jet recording head is provided with a heater having an outermost surface protection layer containing a material selected from the group consisting of metals and metal oxides.
40. The recording unit according to Claim 39, wherein tantalum or tantalum oxide is contained as said material selected

from the group consisting of metals and metal oxides.

41. An ink cartridge comprising ink container portions containing each of said inks constituting an ink set according to any one of Claims 24 to 34.

42. An ink-jet recording apparatus comprising:

an ink container portion containing an ink set comprising at least a black ink and a color ink; and
an ink-jet recording head for ejecting each of said inks supplied from said ink container portion by applying energy to said inks, wherein said ink set is an ink set according to any one of Claims 24 to 34.

43. The ink-jet recording apparatus according to Claim 42, wherein said ink-jet recording head comprises a heater having an outermost surface protection layer containing a material selected from the group consisting of metals and metal oxides, and a device for applying an electrical pulse signal to said heater in response to recording information.

44. The ink-jet recording apparatus according to Claim 43, wherein tantalum or tantalum oxide is contained as said material selected from the group consisting of metals and metal oxides.

45. The ink-jet recording apparatus according to any one of Claims 42 to 44, wherein the ratio of an energy E_{op} , which is input into a heater in order to eject an ink, to the minimum energy input E_{th} , which is necessary for the heater to eject said ink from a recording head, E_{op}/E_{th} , satisfies the following relationship,

$$1.10 \leq E_{op}/E_{th} \leq 1.90.$$

46. An ink for ink-jet comprising:

- (a) a polyvalent metal salt;
- (b) a material selected from the group consisting of acids including amino groups and salts thereof;
- (c) a coloring material; and
- (d) a liquid medium.

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15





FIG. 16





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 12 2858

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 3 776 742 A (SANDERS F) 4 December 1973 (1973-12-04) * claim 1; example 2 *	1-5, 46	C09D11/00 B41J2/175 B41J2/21 B41M5/00
X	EP 0 463 737 A (HEWLETT PACKARD CO) 2 January 1992 (1992-01-02) * claim 1; examples 2,3 *	1,2, 46	
Y	US 5 679 143 A (LOOMAN STEVEN D) 21 October 1997 (1997-10-21) * column 1, line 12 - line 16; claim 1 * * column 6, line 47 - column 7, line 50 * * column 11, line 27 - line 32 * * column 12, line 21 - line 27; tables 1,2 *	6-45	
Y,D	US 5 198 023 A (STOFFEL JOHN L) 30 March 1993 (1993-03-30) * column 1, line 7 - line 12; claims 1,4; tables *	6-45	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7) C09D B41J B41M
Place of search MUNICH		Date of completion of the search 16 November 2001	Examiner Lohner, P
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application I : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/02 (P4/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 12 2858

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

16-11-2001

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 3776742	A	04-12-1973	NONE		
EP 0463737	A	02-01-1992	US	5062893 A	05-11-1991
			CA	2038599 A1	23-12-1991
			DE	69106949 D1	09-03-1995
			DE	69106949 T2	24-05-1995
			EP	0463737 A2	02-01-1992
			HK	130295 A	24-08-1995
			JP	3035379 B2	24-04-2000
			JP	4226175 A	14-08-1992
US 5679143	A	21-10-1997	US	5785743 A	28-07-1998
			CN	1181399 A	13-05-1998
			DE	69704247 D1	19-04-2001
			DE	69704247 T2	19-07-2001
			EP	0839880 A1	06-05-1998
US 5198023	A	30-03-1993	DE	69309162 D1	30-04-1997
			DE	69309162 T2	10-07-1997
			EP	0576151 A1	29-12-1993
			HK	92697 A	01-08-1997
			JP	6057192 A	01-03-1994
			SG	47498 A1	17-04-1998

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82